NOV 28 1980
Item 431-C-13 TD 4.6:29/2/ch.13
dfr
cont'd
341-443
/372
9306

FEDERAL AVIATION REGULATIONS

Department of Transportation
Federal Aviation Administration—Washington, D.C.

CHANGE 13 **EFF. OCTOBER 14, 1980**

Part 29—Airworthiness Standards: Transport Category Rotorcraft

This Change incorporates Amendment 29-20, Airworthiness Review Program—Amendment No. 8A: Aircraft, Engine, and Propeller Airworthiness, and Procedural Amendments, effective October 14, 1980, in Federal Aviation Regulation Part 29.

The effective date of the new material, which is marked by black brackets, is carried at the bottom of each page. Preamble pages and rearranged pages having no new material carry the Change number only.

Page Control Chart

Remove Pages	Dated	Insert Pages	Dated
VII	9/1/77	VII	9/1/77
VIII	12/1/78	VIII	10/14/80
		P-189 thru P-216	Ch. 13
18-1 and 18-2	12/1/78	18-1	10/14/80
		18-2	12/1/78
25 and 26	Ch. 4	25	Ch. 4
		26 and 26-1	10/14/80
		26-2	Ch. 13
67 and 68	12/1/78	67 and 68	10/14/80
69	Ch. 9	69	Ch. 13
70	12/1/80	70	12/1/78
		70-3 and 70-4	10/14/80

Suggest filing this transmittal at the back of the FAR. It will provide a method for determining that all Changes have been received as listed in the current edition of AC 00-44, Status of Federal Aviation Regulations, and a check for determining if the FAR contains the proper pages.

Section *Page*

Instruments Installation

29.1321 Arrangement and visibility ---- 55
29.1322 Warning, caution, and advisory lights ---- 55
29.1323 Airspeed indicating system ---- 55
29.1325 [Static pressure and pressure altimeter systems] ---- 56
29.1327 Magnetic direction indicator ---- 57
29.1329 Automatic pilot system ---- 57
29.1331 Instruments using a power supply ---- 57
29.1333 Duplicate instrument systems ---- 57
[29.1335 Flight director systems] ---- 57
29.1337 Powerplant instruments ---- 57

Electrical Systems and Equipment

29.1351 General ---- 58
29.1353 Electrical equipment and installations ---- 58–1
29.1355 Distribution system ---- 58–1
29.1357 Circuit protective devices ---- 58–1
29.1359 Electrical system fire and smoke protection ---- 58–2
29.1363 Electrical system tests ---- 59

Lights

29.1381 Instrument lights ---- 59
29.1383 Landing lights ---- 59
29.1385 Position light system installation ---- 59
29.1387 Position light system dihedral angles ---- 59
29.1389 Position light distribution and intensities ---- 60
29.1391 Minimum intensities in the horizontal plane of forward and rear position lights ---- 60
29.1393 Minimum intensities in any vertical plane of forward and rear position lights ---- 60
29.1395 Maximum intensities in overlapping beams of forward and rear position lights ---- 60
29.1397 Color specifications ---- 61
29.1399 Riding light ---- 61
29.1401 Anticollision light system ---- 61

Safety Equipment

29.1411 General ---- 62
29.1413 Safety belts: passenger warning device ---- 62
29.1415 Ditching equipment ---- 62

Miscellaneous Equipment

29.1431 Electronic equipment ---- 62
29.1433 Vacuum systems ---- 62
29.1435 Hydraulic systems ---- 63
29.1439 Protective breathing equipment ---- 63
29.1457 Cockpit voice recorders ---- 63
29.1461 Equipment containing high energy rotors ---- 64

Section *Page*

Subpart G—Operating Limitations and Information

29.1501 General ---- 65

Operating Limitations

29.1503 Airspeed limitations: general ---- 65
29.1505 Never-exceed speed ---- 65
29.1509 Rotor speed ---- 65
29.1517 Limiting height-speed envelope ---- 66
29.1519 Weight and center of gravity ---- 66
29.1521 Powerplant limitations ---- 66
29.1522 Auxiliary power unit limitations ---- 67
29.1523 Minimum flight crew ---- 67
29.1525 Kinds of operation ---- 67
29.1527 Maximum operating altitude ---- 67
29.1529 [Instructions for Continued Airworthiness] ---- 67

Markings and Placards

29.1541 General ---- 68
29.1543 Instrument markings: general ---- 68
29.1545 Airspeed indicator ---- 68
29.1547 Magnetic direction indicator ---- 68
29.1549 Powerplant instruments ---- 68
29.1551 Oil quantity indicator ---- 68
29.1553 Fuel quantity indicator ---- 69
29.1555 Control markings ---- 69
29.1557 Miscellaneous markings and placards ---- 69
29.1559 Limitations placard ---- 69
29.1561 Safety equipment ---- 70
29.1565 Tail rotor ---- 70

Rotorcraft Flight Manual

29.1581 General ---- 70
29.1583 Operating limitations ---- 70
29.1585 Operating procedures ---- 70-1
29.1587 Performance information ---- 70-1
29.1589 Loading information ---- 70-1

[Appendix A

[Instructions For Continued Airworthiness] ---- 70-3
Special Federal Aviation Regulation 29 ---- 71
Special Federal Aviation Regulation 29-1 ---- 72

Amendment 29-20

Airworthiness Review Program—Amendment No. 8A: Aircraft, Engine, and Propeller Airworthiness, and Procedural Amendments

Adopted: August 27, 1980 **Effective: October 14, 1980**

(Published in 45 FR 60154, September 11, 1980)

SUMMARY: These amendments to the Federal Aviation Regulations update and improve the airworthiness standards applicable to the type certification of aircraft, engines, propellers, related operating rules, and procedural requirements. These amendments are part of the Airworthiness Review Program.

FOR FURTHER INFORMATION CONTACT:
Marvin J. Walker, Regulatory Review Branch, AVS-22
Safety Regulations Staff
Associate Administrator for Aviation Standards
Federal Aviation Administration
800 Independence Avenue, SW
Washington, D.C. 20591
Telephone: (202) 755-8714

SUPPLEMENTARY INFORMATION:

These amendments are the ninth and last in a series of amendments issued as part of the Airworthiness Review Program. The following amendments have previously been issued as part of this program:

Title and FEDERAL REGISTER (FR) Citation

Amendment No. 1: Form Number and Clarifying Revisions (40 FR 2576; Jan. 14, 1975)

Amendment No. 2: Rotorcraft Anticollision Light Standards (41 FR 5290; Feb. 5, 1976)

Amendment No. 3: Miscellaneous Amendments (41 FR 55454; Dec. 20, 1976)

Amendment No. 4: Powerplant Amendments (42 FR 15034; March 17, 1977)

Amendment No. 5: Equipment and Systems Amendments (42 FR 36960; July 18, 1977)

Amendment No. 6: Flight Amendments (43 FR 2302; Jan. 16, 1978)

Amendment No. 7: Airframe Amendments (43 FR 50578; Oct. 30, 1978)

Amendment No. 8: Cabin Safety and Flight Attendant Amendments (45 FR 7750; Feb. 4, 1980)

These amendments are for the most part based on Notice 75-31 which was published in the FEDERAL REGISTER on July 11, 1975 (40 FR 29410), as well as a number of proposals contained in the following notices of proposed rule making: Notice 75-10 (40 FR 10802; March 7, 1975); Notice 75-19 (40 FR 21866; May 19, 1975); and Notice 75-26 (40 FR 24802; June 10, 1975). Amendments based on the latter three notices have already been issued as a part of the Airworthiness Review Program, specifically those titled Miscellaneous Amendments, Powerplant Amendments, and Airframe Amendments, respectively. Final action on certain of the proposals was deferred, however, at the time the amendments were issued as further consideration and review of these proposals was considered necessary. In other cases, final action was deferred so that they could be considered together with related proposals contained in other notices.

Certain proposals identified as Group 2 in Appendix I to Notice 75-31 were deferred to be dealt with in a later notice as a part of the Airworthiness Review Program. These proposals all addressed the concept of periodically updating the certification basis of airplane models in long-term production. Such recertification every five or ten years would be intended to ensure that the level of safety of all airplanes in service keep pace with the current level of safety expectations. The FAA has now determined that these proposals more appropriately should be examined as a separate issue in a future regulatory action. Accordingly, the proposals identified as Group 2 in Appendix 1 to Notice 75-31 are being dropped from the Airworthiness Review Program.

Proposals relating to cabin safety and flight attendants, which are identified in this amendment, were extracted from Notice 75-31 (40 FR 29410; July 11, 1975) and handled on an expedited basis. Those rules were published in the Cabin Safety and Flight Attendant Amendments (45 FR 7750; February 4, 1980).

Interested persons have been given an opportunity to participate in the making of these amendments and due consideration has been given to all matters presented. The proposals and comments are discussed below. Substantive changes and changes of an editorial and clarifying nature have been made to the proposed rules based upon relevant comments received and further review within the FAA. Except for minor editorial and clarifying changes and the substantive changes discussed below, these amendments and the reasons for them are the same as those contained in Notices 75-10, 75-19, 75-26, and 75-31.

DISCUSSION OF COMMENTS

The following discussions are keyed to the like-numbered proposals contained in Notices 75-10, 75-19, 75-26, and 75-31, and are presented in the same order as the corresponding amendments found in the rules portion of this document.

Proposal 8-1. The proposal to amend § 1.1 in order to transfer the definitions for rated power and thrust to a new § 33.6 is withdrawn. It is considered that such a change may introduce confusion in the administration of aircraft certification rules. See also Proposal 8-94.

Proposal 8-2. Several commenters object to proposed § 21.16(a) which would delete reference to a "novel and unusual design feature" as a necessary condition for the Administrator to issue special conditions. Special conditions become a part of the designated applicable regulations for type certification of a particular product (aircraft, aircraft engine, or propeller).

One commenter indicates that the proposed revision is unjustified and would lead to indiscriminate rule making, and that instead of simplifying the administration of the requirements it would introduce complexity. Another commenter claims that adoption of proposed § 21.16(a) would introduce uncertainty into design requirements.

One commenter suggests that in lieu of revising § 21.16, the FAA should perform a study of § 21.21(b)(2). (Section 21.21(b)(2) provides for denial of a type certificate if an unsafe feature or characteristic exists in the design under consideration. Before adoption of § 21.16, FAA used § 21.21(b)(2) to issue special conditions in letter form.) This commenter suggests that if § 21.21(b)(2) were to continue to be used to issue special conditions to cover an unsafe design feature or characteristic that is not "novel or unusual," it must be equally applicable to a condition that exists on more than one (earlier certificated) product, further stating that the other product or products must then have been type certificated using existing rules which did not adequately cover the unsafe design feature or characteristic. On this premise, the same commenter asks several relevant questions. When § 21.21(b)(2) is applied, does the FAA make it retroactive to the other involved models? Are Airworthiness Directives (Part 39) issued? Why wasn't a special condition issued against the first applicant when the condition was, in fact, novel or unusual? Why was this not followed by a notice of proposed rule making for future application?

These comments and questions caused the FAA to completely reevaluate its practices in designating the applicable regulations for type certification under § 21.17(a), commonly referred to as defining a "type certification basis."

After further consideration of the comments received as well as FAA practice in designating the applicable regulations, and the objectives of proposed § 21.16, the FAA agrees that this proposal should be withdrawn because of the potential for possible abuse of general rulemaking procedures, of the requirements of the Administrative Procedure Act, and the intent of Executive Order 12044. As explained below, the objectives of proposed § 21.16 will be satisfied by the application of a new FAA policy affecting the designation of applicable regulations for the type certification of new aircraft, aircraft

engines, and propeller designs. These future practices are consistent with the FAA General Rule-Making Procedures of Part 11, the Administrative Procedure Act, and Executive Order 12044.

Section 21.16 is one paragraph of a number of paragraphs used to define the type certification basis of a new product. Companion paragraphs of importance to this discussion include §§ 21.17 and 21.21. Section 21.17(a) provides that the applicable airworthiness standards are (1) those requirements of this subchapter that are effective on the date of application for a type certificate, unless otherwise specified by the Administrator or unless compliance with later effective amendments is elected by the applicant or required by special retroactive regulations (e.g., § 25.2), and (2) any special conditions prescribed by the Administrator in accordance with § 21.16. Section 21.16 provides for the issuance of special conditions when the Administrator finds that the existing airworthiness standards do not contain adequate or appropriate safety standards *because of novel or unusual design features* of the product to be type certificated. Section 21.21(b) (1) permits noncompliance with specific provisions of the airworthiness standards when there are compensating factors that provide an equivalent level of safety. Such determinations are commonly referred to as "equivalent safety findings." Section 21.21(b) (2) provides for the denial of a type certificate, notwithstanding a showing of compliance with the applicable airworthiness standards designated in accordance with § 21.17, if the Administrator finds an unsafe feature or characteristic of the product for the category in which certification is requested.

Sections 21.16, 21.17, and 21.21, taken together with FAA policy in designating the applicable regulations must recognize and balance four important considerations: (1) the FAA has an obligation under Section 601 of the Federal Aviation Act of 1958 to keep the airworthiness standards of this subchapter (i.e., FARs 23, 25, 27, 29, 31, 33, and 35) as current as practicable; (2) the type certificate applicant has a right and a need to know, in very specific terms, what the applicable airworthiness standards will be in order to finalize the detail design of its product and to enable the applicant to make reasonable performance guarantees to its potential customers; (3) in the interests of safety, rapid technological advances presently being made by the civil aircraft industry require that the FAA be able to issue special conditions to address truly novel or unusual design features that it has, as yet, not had an adequate opportunity to envisage in the airworthiness standards through the general rulemaking process; and (4) because the airworthiness standards of this subchapter are intentionally objective in nature to allow flexibility in design, the FAA must retain the prerogatives both to make equivalent safety findings and to deny a type certificate whenever an unsafe design feature or characteristic is found during the type certification process.

The phrase "novel or unusual" as used in § 21.16 is a very relative term. As used hereafter in applying § 21.16 to justify the issuance of special conditions, "novel or unusual" will be taken with respect to the state of technology envisaged by the applicable airworthiness standards of this subchapter. It must be recognized that in some areas which will vary from time to time the state of the regulations may somewhat lag the state of the art in new design because of the rapidity in which the state of the art is advancing in civil aeronautical design and because of the time required to develop the experience base needed by the FAA to proceed with general rule making. Applicants for type certification of a new design have the opportunity to mitigate the impact of not knowing the precise airworthiness standards to be applied for "novel or unusual design features" by consulting with the FAA early in their certification planning when such features are suspected or known by the applicant to exist. It should also be recognized that, because of the intentional objective nature of the airworthiness standards of this subchapter, many new design features which might be thought of as "novel or unusual design features" may already be adequately covered by existing regulations, thus obviating the need to issue special conditions.

Henceforth, the special condition will not be issued for general upgrading of the applicable airworthiness standards when novel or unusual design features are not

involved. Whenever the FAA determines that an upgrading of the airworthiness standards of this subchapter is warranted, the upgrading will be promulgated as an amendment to this subchapter consistent with the general rulemaking procedures of FAR Part 11, the Administrative Procedure Act, and Executive Order 12044. Should the FAA conclude that there is a compelling safety need to apply a proposed amendment retroactively to designs already type certificated or to designs for which a type certificate application is in progress, the retroactive aspects of the proposed amendment, if supportable by a regulatory analysis completed in accordance with Executive Order 12044, will be announced in the notice or proposed rule making for that amendment. Public comments on the proposed retroactive aspects will be considered in determining the applicability of the adopted rule.

A number of products for which special conditions have not as yet been issued are undergoing type certification at the time of this amendment. Should the FAA conclude that recent or future amendments to this subchapter should be applied to these products that would not otherwise be applicable under § 21.17(a) (1) then an amendment to require retroactive application will be proposed and acted upon through the general rulemaking process explained above, in lieu of issuing special conditions under § 21.16.

Also, the provisions of § 21.21(b) (2) will no longer be used to justify the issuance of special conditions. However, just as an Airworthiness Directive may be issued under Part 39 to require the correction of an unsafe condition that is likely to exist or develop in a product of the same type design, notwithstanding a showing of compliance with the applicable airworthiness standards, § 21.21(b) (2) may continue to be used to deny issuance of a type certificate if a similar unsafe feature or characteristic is found during the type certification process, notwithstanding a showing of compliance with requirements designated by § 21.17. The unsafe features and characteristics envisaged by § 21.21(b) (2) are those related to specific design configuration or product characteristics of a particular design, that one would not normally expect the applicable airworthiness standards to specifically preclude because of their intentionally objective nature.

It is the practice of the FAA to develop and publish a Type Certificate Data Sheet as an integral part of each type certificate. The type certification basis is recorded on the Type Certificate Data Sheet for public information. In the future the type certification basis statement will identify not only the applicable regulation, including special conditions, but also will identify all exemptions issued pursuant to Part 11, together with "equivalent safety findings" made in accordance with § 21.21(b) (1).

For the above reasons, Proposal 8-2 is withdrawn.

In considering its disposition of the proposal to amend § 21.16(a), the FAA realizes that a "novel or unusual design feature" today may become a common design feature of the future. The issuance of a like special condition for several product designs will most likely compel general rule making on that subject and the history of that special condition could have a very strong influence on thinking when general rule making is initiated. Also, although special conditions are regulations of particular product applicability, they are issued only in the interest of public safety. For these reasons, Part 11, and § 21.16 of Part 21 are amended to require special conditions to be issued in accordance with the existing general rule-making procedures. As is now the case, a docket will continue to be maintained for each set of special conditions, and all material in the docket will continue to be available for public review.

Proposal 8-3. This proposal is one of a group of proposals dealing with the establishment of Instructions for Continued Airworthiness and the responsibilities of maintenance personnel and aircraft operators with respect to those instructions. The group is made up of the following proposals: 8-3, 8-5, 8-21, 8-25, 8-58, 8-62, 8-64, 8-67, 8-77, 8-80, 8-89, 8-91, 8-92, 8-93, 8-97, 8-98, 8-99, 8-104, 8-106, 8-107, 8-110, and 8-111.

A commenter representing a number of scheduled air carriers objects to the requirement in § 21.31(c) that the type design include the Airworthiness Limitations

section of the Instructions for Continued Airworthiness because of the information to be included in that section. Although this commenter does not object to including mandatory replacement times for life-limited parts in the Airworthiness Limitations section, the commenter strongly objects to including inspection intervals and related procedures. Under proposed §§ 43.16 and 91.163(c), the commenter points out, air carriers would be required to comply with these maintenance-related airworthiness limitations. The FAA does not agree that inspection intervals and related procedures can be omitted from the Airworthiness Limitations section of the Instructions for Continued Airworthiness. For example, the proposed Airworthiness Limitations section on a transport category airplane must contain mandatory inspection intervals and related procedures because the damage-tolerance concept described in § 25.571 is predicated upon the use of such inspections to detect initial cracks in principal structural elements before crack growth under repeated loads could progress to a degree which would cause catastrophic failure of the airplane. However, the FAA does agree that §§ 43.16 and 91.163(c) should permit modification of these intervals and procedures by other FAA approved methods. Accordingly, inspection programs approved under §§ 121.25(b), 121.45, 121.367, 123.21(b), 127.13(b), 127.133, 135.5, 135.17, 135.419, 135.421, and 135.425, as defined by approved operations specifications, or an inspection program approved under § 91.217(e) constitute acceptable alternatives. The appendices to Parts 23, 25, 29, 31, 33, and 35 as adopted in this amendment require the applicant to specify (in the Airworthiness Limitations section) mandatory replacement times, inspection intervals, and related procedures. Sections 43.16 and 91.163(c) have been revised to show that only the inspection times and procedures may be adjusted under approved alternative programs.

A commenter objects to § 21.31(c), which in general is applicable to manufacturers, since continued airworthiness, which is covered in the paragraph, is the responsibility of the operator. Because this comment pertains more directly to § 21.50, it is dealt with in conjunction with Proposal 8–5.

In addition to comments relating to the Instructions for Continued Airworthiness, a commenter objects to § 21.31(a) because the proposal to include a list of drawings and specifications in the type design was not mentioned at the Airworthiness Review Conference. In fact, this proposal did appear as an FAA comment on Proposal No. 565 in the Committee I Workbook (titled "Procedures and Special Subjects") made available to all participants at the conference, and may be found in the docket.

Several commenters object to § 21.31(d) because including analyses in the type design—(1) would be redundant, since it is already required as part of the substantiating data; (2) is unnecessary, since the drawings and specifications required under current § 21.31(a) provide the general information needed by the FAA; and (3) introduces the possibility that the FAA would require the manufacturer to provide any and all data used to prepare the drawings and specifications, thereby delaying type certification. The FAA agrees that proposed § 21.31(d) would serve no useful purpose and it is withdrawn.

Proposal 8–4. A commenter objects that § 21.35(b) (2) eliminates flight testing for reliability, contending that analysis and ground test are not dependable as a basis for certification. In the light of this comment, and after further consideration and experience, the FAA has determined that flight testing for reliability does provide safety information not necessarily obtainable from analysis and ground test. Accordingly, the proposal to delete the reference to reliability in § 21.35(b) (2) is withdrawn.

No adverse comment was received on the proposal to replace the word "airplanes" in § 21.35(b) (2) with the word "aircraft" and this amendment to § 21.35(b) (2) is adopted without change.

Proposal 8–5. A commenter objects to the continued airworthiness provisions of § 21.50(b) (and also proposed § 21.31(c)) contending that—(1) continued airworthiness is the responsibility of the operator/owner; (2) current regulations in Parts 23 and 25 already require manufacturers to make available recommended maintenance procedures for the product at the time of its delivery; (3) current operating rules require the operator/owner to establish and comply with a maintenance program; and (4) with respect

to transport airplanes, the present FAA Maintenance Review Board (MRB) system is an entirely satisfactory way of establishing the means for maintaining airworthiness. Current FAA practice allows operators of new transport category airplanes to utilize FAA MRB recommendations (reference FAA Advisory Circular No. AC 121-22) for starting their maintenance programs, and then vary them with FAA approval as experience and operating conditions dictate. The commenter points out that, contrary to that practice, the amendment will require the manufacturer to obtain FAA approval of its recommended maintenance procedures before the airplane is type certificated, and to obtain FAA approval of revisions to those procedures (necessitated by any improvement change in the airplane) before approval of the change itself. This, the commenter states, will impose a severe and unnecessary hardship on the manufacturer.

On the first and second points, although the operator/owner does have responsibility for continued airworthiness, the FAA has found that the recommended maintenance procedures made available under current regulations are frequently inadequate in scope and content, and often do not provide a sound basis for the operator/owner to maintain the airworthiness of the aircraft. The FAA has concluded that the lack of such recommended maintenance procedures can best be remedied by requiring that they be made available to owners and operators by the type certificate or supplemental type certificate holder. On the third point, while it is true that not all operators/owners are required to establish and comply with a continuous airworthiness program, those that voluntarily wish to set up such a program are often handicapped by the lack of comprehensive instructions, which would be remedied by § 21.50(b). On the other hand, those required to establish a program will benefit from the more detailed and comprehensive instructions made available to them under § 21.50(b). On the fourth point, which is directed toward aircraft that will be maintained in accordance with an FAA approved operations specification and maintenance program under Parts 121, 123, 127, 135, or an approved inspection program under § 91.217(e), the FAA recognizes that these procedures for maintaining airworthiness of the products have functioned satisfactorily. In this regard, the FAA expects that operating segments of the air transportation industry would continue to work with type certification applicants in defining adequate maintenance instructions prior to type certification. The FAA MRB document, which is a product of contributions made by both the operators and manufacturer, could be picked up by the type design holder and included as a part of the required Instructions for Continued Airworthiness, thus continuing the usefulness of the existing MRB practices for the original entry into service of new product designs. Likewise, the additional maintenance instructions that would be required and which are not typical to MRB documents, but are presently required in air carrier operators' FAA approved maintenance programs, could also be picked up by the type design holder. Therefore, the screening process that would be utilized by the FAA in reviewing such maintenance documents would not unnecessarily delay type certification or approval of design changes after certification. See also the discussion under Proposal 8-3.

A commenter questions the need for the provision in § 21.50(b) requiring that the Airworthiness Limitations section of the Instructions for Continued Airworthiness be furnished with each aircraft, engine, or propeller. The FAA agrees that this provision is unnecessary, as the type certificate holder must make the manual available, and the operator/owner must comply. To require a manual to be furnished with each equipment would be redundant, and in some instances, would be unnecessary. Accordingly, the requirement that the Airworthiness Limitations section be furnished with each airplane or product is revised to require that the section be furnished to each owner of the type.

A commenter objects to § 21.50(b) insofar as it applies to rotorcraft type certificated under Parts 27 and 29, contending that the manufacturer is already required under those parts to furnish a maintenance manual, which has allegedly been proven adequate. The FAA does not agree. The proposed Instructions for Continued Airworthiness, which are broader in scope and more detailed than the maintenance manual currently required under Parts 27 and 29, would provide the operator/owner with the minimum amount of

information needed to maintain the airworthiness of increasingly complex rotorcraft currently being designed.

A commenter suggests that § 21.50(b) be revised to make it clear that an aircraft manufacturer need not supply Instructions for Continued Airworthiness pertaining to engines and propellers until the complete aircraft is delivered to the first retail purchaser. The continued airworthiness instructions for propellers and engines should be provided to the aircraft manufacturer to facilitate transmittal to purchasers of the aircraft.

A commenter notes that § 21.50(b) would require an aircraft manufacturer to make the Instructions for Continued Airworthiness available to the owner upon delivery of the aircraft and to any other person required to comply with any of the terms of those instructions *upon request.* Since such a request could be made before the first aircraft delivery, it could impose an unnecessary burden on the aircraft manufacturer. The commenter suggests that § 21.50(b) be revised so that such a request need not be filled until after delivery of an aircraft to the first owner. The FAA agrees that an early request for the Instructions for Continued Airworthiness could impose an unnecessary burden on the manufacturer. Additionally, the FAA notes that airplanes can be delivered to an operator, prior to full type certification, with a provisional airworthiness certificate to allow activities such as crew training, and therefore prior to the approval of the Airworthiness Limitations section. Accordingly, the phrase "upon request" has been deleted from § 21.50(b) and the language has been revised to require that at least one set of the complete Instructions for Continued Airworthiness be furnished upon delivery to the customer, or subsequent to issuance of the first standard certificate of airworthiness, whichever occurs later.

Proposal 8-6. Commenters object to the proposal to make § 21.97(b) applicable to all products rather than to engines only because—(1) the volume of paperwork would increase out of proportion to any benefits that might be gained; (2) the applications for supplemental type certificates would be significantly more complex, since there are frequently many configuration variations within an aircraft model and a fleet operator would have to list all of the configurations or make separate application for each; and (3) the term "specific configuration" must be defined if the proposal is to be properly administered. In light of these comments and after further consideration, the FAA concludes that this proposal requires additional study and it is withdrawn.

Proposal 8-7. No unfavorable comment was received on the proposal to amend § 21.123 to require a manufacturer to submit a manual describing its production inspection system and means for controlling materials and parts. Accordingly, the proposal is adopted without substantive change.

Proposal 8-8. A commenter objects to § 21.143(a)(2) contending that substitution of the word "supplier" for "subsidiary" introduces a major change to the requirements, involving increased paperwork and costs. The FAA does not agree. The FAA has consistently administered § 21.143(a)(2) as applying to *all* raw materials, purchased items, parts, and assemblies supplied to the prime manufacturer. The change does not involve increased paperwork or costs because it is a semantic change which clarifies the definition of persons or entities subject to the quality control data requirements of § 21.143, without expanding any of those requirements. The use of the term "subsidiary" is unclear because it implies that there must be a corporate connection between the prime manufacturer and his supplier. Accordingly, the language has been revised to reflect the FAA's intent that the quality control data requirements of § 21.143(a)(2) apply to all "suppliers" of each prime manufacturer. For similar reasons and for internal consistency, § 21.143(b) is revised to replace the term "subsidiary manufacturers" with the term "suppliers".

Proposal 8-9. No unfavorable comment was received on the proposal to amend § 21.182 to ensure that the proposed new § 45.11(c) is cross referenced. Accordingly, the proposal is adopted without substantive change.

Proposal 8-10. A commenter raises the question whether a special flight permit issued under § 21.197(a) (3) would serve as a certificate of airworthiness for international flights. The FAA notes that international flights cannot be conducted under special flight permits issued under § 21.197 unless specifically authorized by the foreign authorities concerned.

Another commenter objects to § 21.197(a) (3) (ii) because as worded, the individual aircraft would have to be flown for at least 50 hours, thereby defeating the purpose of the original proposal (as submitted for the Airworthiness Review) which aimed at eliminating unnecessary delays in obtaining FAA approval of customer demonstration flights. The commenter suggests that this provision be changed to stipulate that the aircraft type must have been flown for at least 50 hours. The FAA agrees that since the proposal concerns aircraft manufactured under a production certificate, and since the aircraft type could have been flown for at least 50 hours during the type certification program, the 50 hours of flight provision is not necessary. However, the FAA does not agree with the commenter's suggested revision. It is necessary to require that production flight tests for the individual aircraft involved be satisfactorily completed before that aircraft is flown on customer demonstration flights. Accordingly, § 21.197(a) (5) is added to prescribe this condition in place of the 50 hours of flight provision.

The same commenter also suggests that § 21.197(a) (3) (ii) should be made applicable to aircraft produced under a type certificate only, since such aircraft received close production surveillance by the FAA. The FAA agrees that a production certificate should not be the limiting factor in obtaining FAA approval of customer demonstration flights. If the aircraft has been demonstrated to otherwise meet all the safety requirements for a standard airworthiness certificate, then customer demonstration flights could be permitted. This proposal is adopted by the addition of § 21.197(a) (5).

In addition, the commenter suggests that proposed § 21.197(a) (3) (ii) be amended with a reference to the maintenance and inspection programs called for under § 21.195 for Experimental and Subpart C Provisional Type Certificates. Such procedures would unnecessarily complicate the issuance of permits for customer demonstration flights and would in effect nullify the original proposal. The portion of the proposal calling for maintenance and inspection programs in these instances is therefore withdrawn.

Proposal 8-11. No unfavorable comments were received on the proposal to amend § 23.253(b) (3) to ensure that high speed buffeting does not become severe enough to prevent the pilot from reading the instruments or controlling the airplane. Accordingly, the proposal is adopted without substantive change. Also see Proposal 8-28.

Proposal 8-12. No unfavorable comments were received on the proposal to amend § 23.361 to redefine the limit engine torque load conditions to be considered for turbine engine installations and to make other clarifying changes. Accordingly, the proposal is adopted without substantive change.

Proposal 8-13. The FAA does not agree with a commenter who suggests that the lead-in of § 23.371 be revised to make the gyroscopic load requirements applicable to piston as well as turbine engines. The FAA has no information to indicate a need for coverage of piston engines in this regulation, nor was any submitted by the commenter.

Another commenter concurs with § 23.371, assuming that a rational analysis of loads under § 23.371(a) is an alternate to the loads specified in § 23.371(b). This assumption is correct. No change to § 23.371 was proposed in this regard. Section 23.371 is adopted without substantive change.

Proposal 8-14. A commenter suggests that the word "operated" in § 23.729(c) be replaced by the word "lowered". The commenter states that the intent of the rule is to ensure that the gear can be lowered in an emergency. The FAA concurs, but the word "extended" is used to preserve the internal consistency of the section. Section 23.729(c) is revised accordingly.

This commenter also questions whether § 23.729(e) would require an "up lock". The commenter is evidently referring to a "lock" in the sense of a positive means other than hydraulic pressure, as required to keep the gear extended by § 23.729(b). Section 23.729(e) contains no such requirement.

Another commenter suggests that the second sentence of § 23.729(e) be revised to add the words "and secured" after the words "fully extended" and "fully retracted" in order to clarify what functions the lights would indicate to the pilot. The first sentence of the paragraph clearly states that the indicators should inform the pilot that the gear is secured in the extended or retracted position.

A commenter states that the proposal is redundant since the requirement is already in effect. The FAA does not agree. This is one of several new provisions being incorporated into the current regulations to assure the reliability of small land-plane landing gear systems.

After further review, the FAA has determined that the words "and warning device" should be removed from the heading of § 23.729(e) to preclude confusion between the requirements of this paragraph and those of § 23.729(f). Section 23.729 is adopted with editorial changes and the revisions discussed.

Proposal 8–15. A commenter objects to § 23.903(f) on the grounds that it imposes new and unjustified criteria for restart capability of reciprocating engine powered airplanes. The FAA believes the requirement to be fully justified. Accidents have occurred with multiengine reciprocating powered, as well as turbine powered airplanes because pilots have not been adequately apprised of the engine restart envelope for their airplane. Therefore, the requirement must apply to both types of engine installations.

This commenter further states that § 23.903(g) is acceptable provided that the "restart requirement is understood to be within the restart envelope for the aircraft (if one is approved for the aircraft)." Present § 23.903(e)(3), as applicable to turbine engine powered small airplanes, states that it must be possible to restart an engine in flight, and § 23.903(f) requires that an approved restart envelope be established. Therefore, development of a restart envelope would be required for the approval of each turbine engine powered small airplane. As adopted, § 23.903(g) requires that, following in-flight shutdown of all engines, electrical power for ignition exists throughout the approved restart envelope.

Another commenter states that it seems inconsistent to require that electrical power be provided for ignition but not for rotational capability sufficient for an engine start. The FAA does not agree. As adopted, the rule provides for those circumstances where engine windmilling speed is sufficient for restarting but insufficient to provide electrical power for ignition.

The proposal is adopted without substantive change. However, § 23.903(f) is revised to make it clear that the specified in-flight engine restart capability is required throughout the required altitude and airspeed envelope.

Proposal 8–16. No unfavorable comment was received on adding a new § 23.905(d) referencing propeller blade pitch control system durability requirements. Accordingly, § 23.905(d) is adopted without substantive change. For discussion of a related proposal to add a new § 35.42, see the discussion under Proposal 8–103.

Proposal 8–17. A commenter suggests that since the requirement for fuel tanks to retain fuel during a landing with landing gear retracted or collapsed may be subject to individual interpretation, advisory material on compliance methods should be reviewed with industry prior to implementation of the rule. The FAA does not agree. The revision merely clarifies an existing requirement. Section 23.967 is adopted without substantive change.

Proposal 8–18. A commenter recommends that the proposal to add a new § 23.991(d) which requires that operation of any fuel pump does not adversely affect continuous engine operation, be withdrawn or its adoption delayed while the compatibility of engine and airplane fuel systems is studied. The compatibility between these systems must be established in the design process, and the relevant design considerations are well known. Delaying the requirement in favor of additional study is not warranted.

Another commenter contends that the requirement is beyond the needs of safety. The FAA agrees that the proposed requirement is too restrictive and § 23.991(d) is revised to provide that the operation of any fuel pump may not affect engine operation so as to create a hazard.

Two commenters disagree with adding a new § 23.991(d), contending that it eliminates present fuel system designs. The FAA has no information to suggest that compliance with the revised section, as discussed above, would be impossible using present fuel system designs, nor was any presented by the commenter.

The proposal is adopted with the revision discussed above.

Proposal 8–19. No unfavorable comments were received on the proposal to amend § 23.1305(n) to permit movement of the propeller blade up to 8° below the flight low pitch position before an indication of the movement is required for the flight crew. Accordingly, the proposal is adopted without substantive change.

Proposal 8–20. For comments related to withdrawal of the proposal to revise § 23.1521(a), see Proposal 8–94.

Proposal 8–21. Since the proposal for § 23.1529 is substantively identical to those for §§ 25.1529 (Proposal 8–58), 27.1529 (Proposal 8–64), and 29.1529 (Proposal 8–77), all comments on these proposals are considered here.

A commenter notes that although the explanation for § 23.1529 makes it clear that the Instructions for Continued Airworthiness need not be finalized until delivery of the first airplane, the proposal itself seems to require that they be finalized before type certification. The commenter suggests that this point be clarified. The FAA agrees, and §§ 23.1529, 25.1529, 27.1529, 29.1529, 31.82, 33.4, and 35.4, are revised accordingly.

In response to a commenter representing a group of scheduled air carriers, the FAA notes that, except for the Airworthiness Limitations section, there is no requirement that any operator/owner use the Instructions for Continued Airworthiness referred to in §§ 23.1529, 25.1529, 27.1529 and 29.1529. Moreover, the new §§ 43.13(a), 43.16, and 91.163(c) allow the use of other methods. In particular, the use of maintenance manuals and continuous airworthiness maintenance programs developed under current Parts 121, 123, 127, and 135, or an inspection program approved under current § 91.217(e), would be acceptable alternatives to the Airworthiness Limitations section. This commenter suggests that language be added to § 25.1529 to make it clear that alternatives to the Instructions for Continued Airworthiness (except the Airworthiness Limitations section) may be used. This suggestion was not adopted because §§ 43.16 and 91.163(c) make this provision sufficiently clear.

Proposal 8–22, 8–23, and 8–24. Final action on Proposals 8–22, 8–23, and 8–24 was taken in Airworthiness Review Program, Amendment No. 7: Airframe Amendments (43 FR 50578; Oct. 30, 1978).

Proposal 8–25. The proposals to add an appendix to Parts 23, 25, 27, and 29 (Proposals 8–62, 8–67, and 8–80) setting forth Instructions for Continued Airworthiness are substantively identical and are discussed below. Unless otherwise stated, the discussion refers to the designated sections in each of the appendices mentioned above.

§ *XX.1(a).* A commenter objects to the concept of specifying requirements (as opposed to providing guidance) for the preparation of Instructions for Continued Airworthiness, contending that such requirements would lead to time-consuming negotiations between the manufacturer and the FAA, and that some flexibility in providing the instructions is necessary. The appendix sets forth, in broad objective terms, the *kinds* of information the Instructions for Continued Airworthiness must contain. Within this framework, the manufacturer would be free to develop detailed instructions appropriate to its aircraft. The FAA is confident that the appendix provides a reasonable measure of flexibility, and anticipates no difficulties or delays in determining the acceptability of the Instructions developed by the manufacturer.

§ XX.1(b). A commenter objects to the requirement that Instructions for Continued Airworthiness be provided for appliances, contending that—(1) this information is often not available from the appliance manufacturer; (2) even when available, the information sometimes has to be revised for the particular application in a manner not approved or intended by the appliance manufacturer; and (3) the information necessary for customized equipment installations would be unreasonably costly to develop. The FAA does not agree. Such information, which is essential to the continued airworthiness of the aircraft, should be provided for each required product. Accordingly, the language of § XX.1(b) is revised to make it clear that if the aircraft manufacturer does not supply continued airworthiness instructions for the product, the Instructions for Continued Airworthiness for the aircraft must include this information. See also the discussion under § XX.3(a) (5) (i).

A commenter objects to the proposal to include information on engines and all appliances in the Instructions for Continued Airworthiness, contending that—(1) such information should be furnished by the engine or appliance manufacturer; and (2) with respect to appliances, only those for which standards have been established by FAA should be covered. On the first point, manufacturers of new engine designs are required to supply the information for their products under new § 33.4. Manufacturers of new aircraft using currently certificated engines are required by § XX.1(b) to provide the information for the engine in their Instructions for Continued Airworthiness for the aircraft. In practice, the FAA expects this information to be developed and supplied by the engine manufacturer. A similar requirement for appliances would be administratively impracticable because of the large number involved. On the second point, it should be noted that specific performance and safety standards have not been established for all essential appliances. However, upon further review, the FAA concludes that it would be unreasonable to require the aircraft manufacturer to cover appliances other than those required in applicable regulations. Accordingly, § XX.1(b), as adopted, refers only to appliances "required by this chapter."

§ XX.2. A commenter suggests a revision of this section to make clear that the Instructions for Continued Airworthiness may consist of a series of volumes, or may be supplied in other than book form, such as on microfilm or microfiche. The language in § XX.2 is sufficiently broad to cover these acceptable alternatives. Reference to the Air Transportation Association of America Specification No. 100 (where it appeared) is deleted from § XX.2(b) because it is nonregulatory.

§ XX.3, lead-in paragraph. A commenter objects to the requirement that the contents of the manual "be prepared to be understood by the persons who will be responsible for maintaining" the aircraft or product, contending that—(1) it would impose a subjective standard that would be impossible to meet; and (2) it could be interpreted to mean that, in some circumstances, manuals for aircraft to be exported must be prepared in the language of the country of export. In light of these comments, the first sentence of the lead-in paragraph of § XX.3, is revised to read as follows: "The contents of the manual or manuals must be prepared in the English language." This conveys the intent of the original proposal. A commenter points out that there may be different levels of maintenance instructions, directed at different classes of operators. For example, the maintenance instructions provided to a fleet operator or commuter airline may be more comprehensive than those provided to a fixed base operator. Any level of maintenance instructions considered appropriate by the manufacturer may be submitted, provided that those instructions comply with the minimum standards in the appendix.

§ XX.3(a) (2). A commenter recommends that the requirement for complete descriptions be limited in scope to the "standard" aircraft and "quantity-installed" optional equipment, contending that it would be virtually impossible to devise "custom" maintenance manuals for each product because of the many combinations of equipment that may be ordered by the purchaser. In addition, the commenter states that a manual containing all of these combinations would be difficult to use. The FAA does not agree. To achieve its purpose, the Instructions for Continued Airworthiness must contain information on each item of equipment required by regulation to be installed on the

aircraft. The FAA notes that supplemental type certificates (STC's) are required for installation of equipment not a part of the type certificate, and that this maintenance manual requirement is equally applicable to the STC applicant.

§ *XX.3(a) (3).* A commenter recommends that since maintenance personnel have no need for the kind of operating information provided in a Pilot's Operating Handbook, the paragraph be revised to require only *basic* principles of equipment control and operation. The FAA agrees, and § XX.3(a) (3) now refers to "basic control and operation information."

§ *XX.3(a) (5) (i).* A commenter recommends that applicants be allowed to refer to a component manufacturer as a source of information instead of including the information in the Instructions for Continued Airworthiness. The commenter argues that many component manufacturers prefer to maintain control of their maintenance information to ensure that it is up to date. In other cases, maintenance at the factory may be required because of the complexity of the equipment. The FAA recognizes that some accessories, instruments, and equipment have an exceptionally high degree of complexity, requiring specialized maintenance techniques, test equipment, or expertise. In such cases, it would be in the interest of safety to allow the applicant to refer to the appropriate manufacturer in the maintenance instructions. The FAA does not agree, however, that such reference should be allowed in other circumstances. Section XX.3(a) (5) (i) (redesignated § XX.3(b) (1)) is revised accordingly.

A commenter recommends that the last sentence of § XX.3(a) (5) (i), be revised to allow reference to a separate inspection program, rather than include it in the maintenance instructions, so that the inspection program could be better kept current and also tailored to an individual operator's needs. The FAA does not agree. The inspection program must be set forth in the Instructions for Continued Airworthiness to ensure its availability to those who will benefit from it.

The FAA, after further study of § XX.3(a) (5) (i), has decided that the provision should specifically require a description of applicable maintenance or wear tolerances. Section XX.3(a) (5) (i) (redesignated § XX.3(b) (1)) is clarified in this regard.

§ *XX.3(a) (5) (ii).* A commenter objects to the words "could occur" in this paragraph because it encompasses everything within the realm of possibility, thereby unnecessarily increasing the volume of the maintenance instructions. The phrase "probable malfunctions" replaces the phrase "typical malfunctions that could occur" in § XX.3(a) (5) (ii) (redesignated § XX.3(b) (2)).

§ *XX.3(a) (5) (iii).* A commenter suggests that this paragraph would be clearer if the first three words and the last five words are deleted. Section XX.3(a) (5) (iii) (redesignated § XX.3(b) (3)) is revised accordingly.

§ *XX.3(a) (5) (iv).* A commenter suggests revision of this paragraph to make it clear that the overweight landing check refers to the condition in which a certificated landing weight is lower than certificated takeoff weight, since the aircraft manufacturer cannot speculate what damage might be done to an aircraft that takes off and must immediately land at a weight near the certificated takeoff weight. This comment may have merit for certain aircraft. Moreover, since an overweight landing is but one of several occurrences which would necessitate a check to determine aircraft damage, to single out one occurrence would imply that the others need not be covered in the maintenance instructions. Accordingly, the words "checks after an overweight landing" are deleted from § XX.3(a) (5) (iv) (redesignated § XX.3(b) (4)).

§ *XX.3(b).* A commenter recommends deletion of the requirement for an overhaul manual or section, contending that—(1) there are many products that, for safety reasons, should not to be overhauled; and (2) the manufacturer must make the technical assessment as to whether a product can be safely overhauled. In the light of these comments, and after further consideration, the FAA finds that those portions of § XX.3(b) that provide for overhaul information only (except for engines), should not be required in the Instructions for Continued Airworthiness. Accordingly, §§ XX.3(b) (1) (i), XX.3(b) (1) (ii),

XX.3(b) (1) (iv), XX.3(b) (1) (viii), and XX.3(b) (3), are withdrawn. The other provisions of § XX.3(b) specify information that is needed for purposes other than overhaul.

§ XX.3(b) (1) (iii). No adverse comment was received on this proposal to require structural access plate information. Accordingly, it is adopted as proposed, but redesignated § XX.3(c).

§ XX.3(b) (1) (v). No adverse comment was received on this proposal to require instructions on special inspection techniques. Accordingly, it is adopted as proposed, but redesignated § XX.3(d).

§ XX.3(b) (1) (vi). A commenter points out that no part can be restored to its original condition by protective coatings or treatments. The FAA agrees, and § XX.3(b) (1) (vi) (redesignated § XX.3(e)) is revised to make this clear and to require only the information necessary to apply protective treatments to the structure after inspection.

§ XX.3(b) (1) (vii). No adverse comment was received on this proposal to require data on structural fasteners. Accordingly, it is adopted as proposed, but redesignated § XX.3(f).

§ XX.3(b) (1) (ix). No adverse comment was received on the proposal to require a list of special tools. Accordingly, it is adopted as proposed, but redesignated § XX.3(g).

§ XX.3(c). Three commenters object to the concept of supplying generalized repair data. One contended that—(1) the nature of the damage may not be known in a particular case, though it may appear to fall under a general repair "fix"; (2) the safety of the product may be seriously impaired by repairs made in such instances; and (3) the manufacturer can provide alternate means for a mechanic to obtain repair data. In the light of these comments, the FAA agrees that it is not necessary to include the repair information in the Instructions for Continued Airworthiness as proposed. Accordingly, proposed § XX.3(c) is withdrawn.

§ XX.4. A commenter suggests that the manufacturer should be allowed to list items in the Airworthiness Limitations section that it deems necessary to maintain structural integrity, where such items are not called out in the applicable airworthiness standards. Another commenter, representing the scheduled airlines, objects to the inclusion, in the Airworthiness Limitations section, of mandatory replacement times for parts other than life-limited parts and of mandatory inspection intervals. The resolution of these comments is discussed under Proposal 8-3. The language proposed for the Airworthiness Limitations sections of the appendices to Parts 23, 25, 27, and 29 is being retained, except that the mandatory replacement times, mandatory inspection intervals, and related procedures are specified as those associated with structural integrity—including those approved under current § XX.571. It also is made clear that FAA approved alternative programs may be used. To avoid unnecessary restriction being placed on operation, only these items are listed in the pertinent Airworthiness Limitations section. Other items can of course be listed in other sections of the Instructions for Continued Airworthiness.

Proposal 8-26. The addition of new §§ 25.101(i) and (j) would set forth requirements for automatic systems that affect performance, including automatic takeoff thrust control systems (ATTCS). In view of the evolving technology of automatic systems, the special features and functions of each design, and the complex interrelationships with other systems, the FAA has concluded that specific regulations are premature and that safety considerations can be more advantageously addressed in special conditions for specific systems. Accordingly, Proposal 8-26 and related Proposals 8-34, 8-48, and the § 25.1305(c) (9) portion of 8-50 are withdrawn.

Proposal 8-27. The revision of § 25.111(c) (4) will permit changes in power or thrust by an automatic takeoff thrust system but prohibit any change requiring action by the pilot when determining the takeoff path. Although specific proposals relating to criteria for automatic takeoff thrust systems have been withdrawn, the FAA believes that this proposal should be retained as it standardizes the procedure for determining the takeoff path, and is consistent with current practice.

One commenter implies that this rule change will add the task of monitoring conditions and instruments and thereby increase the pilot workload. Other commenters suggest that a limited provision for manual throttle setting be included, or are opposed to the proposal completely on the grounds that safety will be compromised in service. Since the rule will apply in the context of a determination of performance rather than an operating requirement, the proposal is adopted without change.

Proposal 8-28. A commenter suggests that the term "impair" in § 25.253(a) (2) (iii) be changed to "significantly impair". The FAA does not agree. In present high altitude, high Mach number jet airplanes, any recovery from upset or speed anomaly must be done essentially by reference to flight instruments. Therefore, any buffet or vibration condition which would in any way impair the pilot's ability to accurately interpret instrument information cannot be tolerated. The same commenter stated that some interpretative material on vibrational frequencies and levels of acceleration would be useful. Use of interpretative material would divert attention from the primary consideration, impairment of pilot ability, which is qualitative. Proposed § 25.253(a) (2) (iii) is adopted without substantive change.

Proposal 7-17. Although no unfavorable comment was received on the proposal to amend § 25.305(d), two commenters state that their agreement was with the understanding that both the discrete gust and the continuous turbulence analyses are required. Present § 25.341(a) requires that limit load factors be established by reference to a discrete gust encounter. Present § 25.305(d) specifies that the dynamic response of the airplane to vertical and lateral continuous turbulence must be taken into account. Both analyses are required.

Two commenters recommend that present § 25.341 be amended to require dynamic loads analysis by reference to discrete gusts having varying gust gradient distances. The FAA does not agree. The combination of discrete gust analysis under § 25.341 and continuous turbulence analysis under § 25.305 is less complex than the method described by these commenters and provides sufficient substantiation of strength. The proposal is adopted without substantive changes.

Proposal 8-29. Many negative comments were received on the proposal to revise § 25.307(a) to require ultimate load tests for each normal and fail-safe critical load condition. Three commenters indicate that the proposed regulation would add to the cost and time required for certification although present airplane safety records do not support the need for a change. One commenter points out that the design philosophy used for commercial transports, due to the dominant influence of the economic requirement for long life without structural fatigue problems, often produces reserve margins of safety. Another commenter proposes that ultimate load tests be limited to structures such as composites, which substantially differ from conventional structure. The FAA agrees that to conduct ultimate load tests for all critical load conditions would greatly increase the amount of testing required, which is not warranted by the safety record since there have been no service features which indicate that present methods of substantiation are inadequate. In many cases failures in service result from conditions such as fatigue or corrosion which are not covered by ultimate load tests. The proposal to require ultimate testing of all structural components therefore is deleted. In some cases, however, analysis must be supplemented by limit and/or ultimate load tests. The amendment, as adopted, is revised accordingly.

Proposal 8-30. Several negative comments were received on §§ 25.365(e) and (f), requiring airplane designers to consider pressure vessel decompression resulting from the loss of any nonplug door, detonation of a bomb within the cabin at all probable locations, and engine disintegration. Several commenters oppose designing for the loss of a nonplug door, stating that there is no reason why nonplug doors cannot be designed to be as safe as plug doors. These commenters suggest that the door design criteria be upgraded to improve door integrity. The FAA agrees that door integrity should be improved to the extent that design for their loss is not justified. Therefore § 25.783 is revised in response to Proposal 8-35 to require this improved level and § 25.365(e) (1) is withdrawn.

Many commenters object to designing for all possible bomb detonations and probable bomb locations. A commenter points out that airworthiness requirements in the past have attempted to safeguard aircraft against structural and mechanical failure, human error, natural hazards, etc. They note that no one has attempted to incorporate into airworthiness requirements the consequences of homicidal or suicidal tendencies. Another commenter states that the aircraft industry has to accept responsibility for compensating the public for loss or injuries resulting from defects in its products, and the inclusion of a bomb damage requirement in Part 25 could significantly extend the grounds of possible product liability actions, particularly with the imprecise requirements of § 25.365(e). Many commenters state that the wording of § 25.365(e) (3) is so vague as to make its implementation impossible. The FAA notes that, ultimately, minimizing the loss of airplanes as a result of bomb explosions is a ground security problem.

A commenter suggests an alternative to § 25.365(e) (3) which would establish a relationship between the design maximum opening and the cross-sectional area of the pressurized shell. The FAA agrees that the proposed relationship provides an acceptable method for determining hole size. The FAA has determined that the maximum hole size required should be 20 square feet, a value contained in Airworthiness Directive 75-15-05 (August 11, 1975) pertaining to openings in wide-body transports. Section 25.365(e) (3) is revised to allow the maximum opening to vary as a function of the cross-sectional area of the pressurized shell to account for the differences in size between narrow and wide-body transports and is redesignated and adopted as § 25.365(e) (2).

The FAA finds that the maximum opening specified in adopted § 25.365(e) (2) will exceed the opening that would result from causes other than bomb explosions or engine disintegration, and that a probability safety analysis to determine hole size in passenger or cargo areas resulting from other causes is not needed. Thus, proposed § 25.365(f) is withdrawn.

In light of the comments received on proposed § 25.365(e) (4), and after further consideration, the FAA concludes that openings caused by airplane or equipment failure can occur in any compartment, and that partitions, bulkheads, and floors should be designed for openings from these causes. Thus, proposed § 25.365(e) (4) is revised accordingly, redesignated, and adopted as § 25.365(e) (3).

No adverse comments were received on proposed § 25.365(e) (2) to require design to withstand penetration of the cabin by a portion of an engine following engine disintegration and the proposal is redesignated § 25.365(e) (1) and adopted without substantive change.

Amendment to § 25.571(a) (3). Because of the change to § 25.1529 adopted in this amendment, the reference to the "maintenance manual" in § 25.571(a) (3) is no longer appropriate. For consistency, § 25.571(a) (3) references the Airworthiness Limitations section of the Instructions for Continued Airworthiness.

Proposal 8-31. Numerous unfavorable comments were received on the proposal to add a new § 25.633 requiring that essential systems be designed to minimize damage caused by detonation of a bomb in the airplane. Most commenters contend that there is no means to protect essential systems from all possible bomb detonations and that bomb size and location cannot be rationally defined. Several commenters indicate that the separation of essential systems on modern airplanes presently provides a measure of protection and that the proposed requirements of § 25.633 are beyond the state of the art.

The FAA agrees that a rational means of determining and defining all possible bomb size/location combinations which would damage essential systems does not exist. Therefore, the proposal is withdrawn.

Proposal 8-32. Several commenters object to the proposed horizontal stabilizer "trim-in-motion" aural warning requirement of § 25.677(e) on the grounds that the aural environment in today's cockpits is already cluttered and that finding new and distinctive aural warnings is becoming difficult. They further suggest that small increments of trim change should not cause aural warning, and that warnings should be given only when a

safety-of-flight hazard exists. One commenter suggests that there is no need for separate aural warning on aircraft having direct trim control wheels in the cockpit.

The FAA agrees with the comments and upon further review concludes that the proposal is premature and unworkable. Accordingly, it is withdrawn for further study.

Proposal 8-33. Several adverse and supporting comments were received on the proposal to add a new § 25.685(e) requiring arrangement of control systems to provide an airplane with the capability of continued safe flight and landing in the event of an inflight localized structural failure. Several commenters agree with the intent of the proposal and propose minor changes. One commenter agrees with the intent of the proposal, but believes that only failures which have not been shown to be extremely improbable need be considered. Commenters state that the intent of the proposed rule change is already encompassed by § 25.365(e) which would require that floor failure resulting from rapid decompression be shown to be extremely improbable.

A commenter further states that present § 25.671(c) requires control systems to be designed to be tolerant of failures, and that control system damage is more likely from other sources. The commenter claims that service experience and rational analysis show that the floor structure provides the best available protection for the control system from damage from these other sources.

After further study the FAA agrees with the commenters that the primary objectives of this proposal are adequately covered by several existing sections of FAR 25. For example: § 25.365(e) requires that the floor be designed for pressure vessel opening which is a function of the cross-sectional area of the fuselage; § 25.571 requires all structure to be damage tolerant where practical; § 25.671 requires that control systems be tolerant of failures, including exterior damage; § 25.629 requires freedom from flutter under failure conditions; § 25.631 requires protection of controls in the empennage structure from bird strikes; and § 25.901(d) requires design precautions be taken to minimize the hazards to the airplane, including control systems, in the event of an engine rotor failure. The proposal therefore is withdrawn.

Proposal 8-34. For an explanation of the withdrawal of the proposals concerning automatic systems that affect airplane performance, one of which is the proposal to add a new § 25.705, see Proposal 8-26.

Proposal 8-35 and 2-59. Several commenters object to the requirement in § 25.783(e) that provisions for the inspection of door locking mechanisms must be discernable under all possible lighting conditions. The commenters state that allowance should be made for use of supplemental lighting such as a flashlight to aid in the inspection. The FAA agrees and the section is revised accordingly.

A commenter states that direct visual inspection is only needed for external doors for which the initial opening movement is not inward and which are pressurized or for which an inadvertent opening could prevent continued safe flight and landing. Although these comments have merit, they go beyond the scope of Proposal 8-35 and interested parties have not had an opportunity to comment on these changes. No change to the section is being made based on these comments. Several commenters object to the redundancy of a dual warning system requirement and state that in lieu of redundancy, a reliability level should be specified. Further comments state that all external doors do not require this level of reliability. The FAA agrees that this reliability level could be specified and should apply only to external doors for which initial movement is not inward, and the section is changed accordingly. The present language defining where door warning systems are required is retained, as no change in present practice is intended.

A commenter suggests that § 25.783(e) should specify several good design practices. These design practices are desirable but are not essential, since the necessary level of safety can be obtained by alternate means under § 25.783.

Several commenters object to new § 25.783(f), suggesting that it apply only to nonplug type doors and doors whose loss would present a probable hazard. The FAA agrees that provisions to prevent unsafe pressurization can be limited to doors whose loss would

present a probable hazard. However, the FAA does not agree that it should be limited to nonplug type doors because a plug door is defined as one whose initial opening is inward and this feature does not necessarily provide complete assurance that an unsafe pressurization will not occur with subsequent opening of the door in flight. The clarifying phrase "to an unsafe level" has been added to § 25.783(f). The intent is to prevent pressurization to a level which would be hazardous if an unlocked external door inadvertently opened.

Several commenters object to proposed new § 25.783(g) (Proposal 8-35), stating that it would unnecessarily preclude the use of nonplug type doors above 45,000 ft. The FAA agrees that nonplug type doors can safely be used at altitudes above 45,000 ft., since adequate warning systems and door integrity are provided by § 25.783(e). Proposed new § 25.783(g) is withdrawn.

A commenter proposes that for the door whose opening would be a hazard, the door and immediate surrounding fuselage, door mechanisms, and warning system be designed for any combination of failures (including improper operation) not shown to be extremely improbable. The FAA agrees. In place of the proposals in 8-30, with regard to §§ 25.365(e) (1), (3), and (4), a rule is included to require determination by safety analysis that inadvertent opening of doors which could prevent continued safe flight and landing is extremely improbable.

Two commenters state that the criteria for passenger egress in the revision to the second sentence of § 25.783(g) (Proposal 2-59 of Notice 75-10) should be evacuation time, and not the rate of passenger egress through a given exit. The FAA agrees. Revision of the second sentence of § 25.783(g) is redesignated as § 25.783(i) and the reference to § 25.561(a) (3) in the proposal is corrected to reference § 25.561(b) (3).

Numerous negative comments concern proposed new § 25.783(j), which requires that lavatory doors open into the cabin to preclude anyone from being trapped in the lavatory. The commenters state that this requirement is overly restrictive on design and that an outward opening door could have an adverse effect on aisle width and emergency evacuation capabilities if such a door jammed open. The FAA agrees that inward opening doors can be designed to prevent anyone being trapped in a lavatory in cases of incapacitation or for other reasons. Thus, new § 25.783(j) is revised to delete the requirement that lavatory doors open into the cabin.

Proposals 8-36, 2-60, and 8-37. Final action on Proposals 8-36, 2-60, and 8-37 was taken in Airworthiness Review Program, Amendment No. 8: Cabin Safety and Flight Attendant Amendments (45 FR 7750; February 4, 1980).

Proposal 8-38. One commenter objects to adding a new § 25.792 to require a sign indicating whether lavatories are occupied, asserting that it would be inappropriate for general aircraft certificated under Part 25. Two commenters doubt that the proposed rule would achieve the objective of preventing aisle congestion near lavatories. They point out that many existing aircraft have similar signs which have not prevented people from "standing in line" for lavatories. Also, passengers can cause congestion in aisles for other reasons. One of the commenters states that lighted signs in a darkened cabin; i.e., during movies or rest periods, would annoy passengers, and that the rule might foster a proliferation of signs throughout the cabin. Finally, one commenter is concerned that any increase in the number of lighted signs might distract the passengers' attention from more essential notices.

Based on the comments and upon further review, the FAA finds that the proposed requirement would not achieve the objective sought. Accordingly, the proposal is withdrawn.

Proposal 8-39. Final action on Proposal 8-39 was taken in Airworthiness Review Program Amendment No. 8: Cabin Safety and Flight Attendant Amendments (45 FR 7750; February 4, 1980).

Proposal 8-40. Final action on Proposal 8-40 was taken in Operations Review Program Amendment No. 8 (45 FR 41586, June 19, 1980).

Proposal 8-41. A commenter suggests that new § 25.851(a) (5), which replaces current § 25.853(f), be expanded to prescribe four fire extinguishers for a passenger capacity of 100 or more, and to require at least one CO_2, dry chemical, or all purpose fire extinguisher near lavatory and galley areas. These suggested changes are beyond the scope of the notice. However, changes in these requirements are appropriate and the FAA is conducting a research program to establish comprehensive standards and guidance information pertaining to the selection of portable fire extinguishers, taking into consideration types and quantities of extinguisher agents, extinguisher performance, and other factors. Regulatory changes based on the findings of this research program will be proposed in the next airworthiness standards review.

Sections 25.851(a) (5) and (a) (6), which consolidate hand fire extinguisher requirements, are adopted without substantive change.

Proposals 8-42, 2-18, 2-65, 2-114, and 2-160. Final action on Proposals 8-42, 2-18, 2-65, 2-114, and 2-160 was taken in Airworthiness Review Program, Amendment No. 8: Cabin Safety and Flight Attendant Amendments (45 FR 7750; February 4, 1980).

Proposal 8-43. Final action on Proposal 8-43 was taken in Airworthiness Review Program, Amendment No. 7: Airframe Amendments (43 FR 50578; October 30, 1978).

Proposal 8-44. For a discussion of proposed § 25.905(c), see the discussion under Proposal 8-103. The proposal to add a new § 25.905(c) is adopted without substantive change.

Proposals 8-45 and 8-96. The proposed amendments to §§ 25.939 and 33.65 are being deferred for consideration in a forthcoming notice of proposed rule making of the Aircraft Engine Regulatory Review Program.

Proposals 8-46, 3-35, and 8-47. Final action on Proposals 8-46, 3-35, and 8-47 was taken in Airworthiness Review Program, Amendment No. 7: Airframe Amendments (43 FR 50578; Oct. 30, 1978).

Proposal 8-48. For an explanation of the withdrawal of the proposals concerning automatic takeoff thrust control systems, one of which is the proposal to add a new § 25.1143(f), see Proposal 8-26.

Proposals 8-49 and 3-41. Final action on Proposals 8-49 and 3-41 was taken in Airworthiness Review Program, Amendment No. 7: Airframe Amendments (43 FR 50578; Oct. 30, 1978).

Proposal 8-50. For an explanation of withdrawal of the proposals concerning automatic takeoff thrust control systems, one of which is the addition of a new § 25.1305(c) (9), see Proposal 8-26.

One commenter objects to revising § 25.1305(d) (1), stating that significant aerodynamic forces acting on the powerplant nacelle make the direct measurement of thrust impractical. The FAA agrees that such forces may be significant. This commenter further objects to the revision, stating that it is beyond the state of the art to prohibit a parameter from being used if the accuracy of the indication will be adversely affected by any engine malfunction or damage. The FAA agrees that precise values of thrust provided by a malfunctioning, damaged, or deteriorated engine are unnecessary, provided that any changes in thrust due to engine malfunction, damage, or deterioration are indicated to the pilot. The paragraph is revised to require that the indication must be based on the direct measurement of thrust or of parameters that are directly related to thrust.

Although concurring with § 25.1305(d) (1), one commenter states that he would prefer to retain the existing requirements and delete the words ",or to indicate a gas stream pressure that can be related to thrust,". The FAA does not agree. The change suggested by this commenter would eliminate the requirement for thrust information and would retain the requirement for change-of-thrust information only. It also would provide a lower level of safety than the adopted paragraph.

This commenter also states that § 25.1305(d) (1) should be complementary to a similar requirement in Part 33 of this chapter. The FAA does not agree. In current practice, the airframe manufacturer determines how performance should be met. The choice of a

means to indicate thrust is negotiated between the airplane manufacturer and the engine manufacturer. The factors which influence the final choice are substantial and may vary among airplane designs. These factors may not be known to the engine manufacturer at the time of engine type certification. Another commenter states that the need for an actual value of thrust is not obvious, whereas indication of a loss of thrust would satisfy the original proposal. The FAA agrees that the actual value of thrust is of little value to the pilot. Section 25.1305(d) (1) is revised to specify that the indicator indicate thrust, or a parameter related to thrust, to the pilot.

Proposal 8-51. No unfavorable comments were received on the proposal to change the reference in § 25.1307(h) for fire extinguishers in connection with Proposal 8-41. Accordingly, the proposal is adopted without substantive change.

Proposal 8-52. Final action on Proposal 8-52 was taken in Airworthiness Review Program, Amendment No. 8: Cabin Safety and Flight Attendant Amendments (45 FR 7750; February 4, 1980).

Proposal 8-53. Several commenters point out a number of service deficiencies with proposed § 25.1421 which defines the requirements for cargo compartment fire detection systems. They contend that the requirement for the detection system to actuate a warning within one minute of the start of a fire is too restrictive. One commenter cites the results of FAA tests which show average fire detection times to be from 1.75 to 5 minutes. The commenters also suggest that the tests necessary to show compliance with the warning requirements are not clearly defined. Finally, one commenter points out that fires in baggage containers and other enclosed containers can burn for a considerable time before detection is likely by fire detectors in the cargo compartment.

The FAA does not concur that the one-minute requirement is too restrictive. A survey of fire detection technology has indicated that the state of the art permits detection of a fire in less than one minute after inception. In addition, current standards do not define the test procedures necessary to show compliance with warning requirements. The new one-minute requirement is intended to improve the standards in this regard.

The proposal is adopted without substantive change.

NOTE: This proposal has been carried erroneously under § 25.1421 which pertains to megaphones. It will be included in the amendment as a new § 25.858.

Proposal 8-54. Comments received from several commenters reflected confusion over the intent of proposed § 25.1439(c). It was noted that much of what was intended by proposed § 25.1439(c) is included in existing § 25.1439(a) as amended by Amendment 25-38 (41 FR 55454; 12/20/76), provided that the portable oxygen requirements of § 25.1447(c) (4) are retained. Amendment 25-38 emanated from Airworthiness Review Program Notice No. 2 (40 FR 10813; 3/7/75), and was adopted (41 FR 55468; 12/20/76) after publication of Airworthiness Review Program Notice No. 8 (40 FR 29420; 7/11/75) which contained proposals 8-54 and 8-55. The FAA agrees that the existing regulations require much of what was intended by proposal 8-54, provided that proposal 8-55 is withdrawn. The FAA further agrees that additional clarifications are needed before further amendments are made to § 25.1439. Therefore the FAA withdraws both proposals 8-54 and 8-55. The subject of protective breathing equipment will be addressed in a forthcoming notice of proposed rule making.

Proposal 8-55. The proposal to delete § 25.1447(c) (4) is withdrawn for the reasons stated for withdrawal of Proposal 8-54.

Proposal 8-56. For comments related to the proposal to revise § 25.1521(a), and for the withdrawal of that proposal, see Proposal 8-94.

Proposal 8-57. Final action on Proposal 8-57 was taken in Airworthiness Review Program, Amendment No. 7: Airframe Amendments (43 FR 50578; October 30, 1978).

Proposal 8-58. For comments related to the proposal to amend § 25.1529, see Proposal 8-21.

Proposal 8-59. A commenter objects to the proposed new § 25.1557(e), calling for a placard on each flight attendant seat to indicate that it may be occupied by a flight

attendant, asserting that such placarding is redundant and that a proliferation of placards in the aircraft will only serve to confuse the passengers and make all placards less effective. The commenter also states that the proposal would prohibit non-flight attendant airline personnel who are cognizant of emergency procedures from occupying flight attendant seats when the aircraft is full. The FAA concludes that a new aircraft certification rule is unnecessary to achieve this result and the proposal is withdrawn.

Proposals 8-60 and 8-61. Final action on Proposals 8-60 and 8-61 was taken in Airworthiness Review Program, Amendment No. 7: Airframe Amendments (43 FR 50578; October 30, 1978).

Proposal 7-55. A commenter recommends that discrete gusts with varying gradient distances be added as a supplement to Appendix G to Part 25. The FAA disagrees because past experience with the use of discrete gusts with varying gust gradient distances has indicated that knowledge with regard to how gust intensity varies with gust gradient distance is not currently available to the designer. The research and development work accomplished in the area of dynamic response to continuous turbulence has indicated that the continuous turbulence criteria of Appendix G to Part 25 is the most rational approach currently available which gives consistent strength levels for airplanes of different characteristics and missions.

A commenter recommends that paragraph (a) of Appendix G be revised to delete the requirement for considering combined stresses based on both vertical and lateral components of turbulence. The commenter states that the current practice of combining root-mean-square stresses (shear, moment, and torsion) resulting from gust calculations involving only purely vertical or lateral components of turbulence is a realistic, practical method for combining stress. The commenter contends that the methods for realistically combining statistical load quantities involving both vertical and lateral components of turbulence have not been satisfactorily developed in the current state of the art. After further review the FAA agrees. Paragraph (a) of Appendix G is revised to delete the requirement for considering the combined stresses resulting from the vertical and lateral components of turbulence.

A commenter recommends that paragraph (b) (3) (i) of Appendix G be revised to require a gust intensity of $U\sigma = 75$ fps gust velocity in the interval 0 to 20,000 ft. altitude with a linear decrease to 30 fps at 80,000 ft. altitude. This recommendation would obviate the need to do mission analysis to justify lower levels of loads than those required to meet the design envelope gust intensity factor of 85 fps for new airplanes whose characteristics are similar to previous designs which have been shown to be adequate for the lower level of gust intensity being proposed. There is no technical need for new aircraft which are similar to existing aircraft with regard to response characteristics and basic mission profiles to make extensive mission analysis computations in order to establish their adequacy with regard to loads resulting from encounters with continuous turbulence if they are designed for the gust intensity shown to be adequate for the existing design. Therefore, it is acceptable to use a gust intensity value of 75 fps from 0 to 20,000 ft. altitude, and a linear reduction from 75 fps at 20,000 ft. to 30 fps at 80,000 ft., provided the new design is comparable to a similar design with extensive satisfactory service experience. These criteria, which have been under discussion between FAA and industry for over 10 years, are proposed as new rules rather than acceptable means of complying with existing rules. Paragraph (b) (3) (i) is revised accordingly. The commenter also recommends that paragraph (d) (1) be revised to require a gust intensity of $U\sigma = 60$ fps on the interval 0 to 20,000 ft. altitude and be linearly decreased to 23 fps at 80,000 ft. altitude. The FAA disagrees. The gust intensities in paragraph (d) (1) are based on the distribution of gust intensity with altitude which were developed in the basic research for the development of continuous turbulence criteria and are, therefore, considered reasonable as a lower design envelope limit for mission analysis. A cost analysis was provided by the commenter to justify the lower gust intensities, but the FAA finds that this cost analysis was based on "design envelope analysis" alone. Paragraph (c), which is an alternative to paragraph (b), provides for a "mission analysis". Actual experience has

shown that "mission analysis," which considers airplane operational characteristics, has been used in the past in lieu of the 85 fps intensities to prevent weight and cost penalties. Paragraphs (c) and (d) of Appendix G are adopted without substantive change.

A commenter recommends that paragraph (d) of Appendix G be revised to delete the reference to "fail-safe loads" since such loads are not provided in Appendix G. The FAA agrees. Paragraph (d) of Appendix G is revised accordingly.

A commenter recommends that proposed paragraph (e) of Appendix G be deleted since acceleration levels measured at the pilot station on current conventional aircraft can be established by flight demonstration much more easily and with less cost than by use of an expensive analysis considering response to continuous turbulence. Upon further review, the FAA has determined that it lacks sufficient information to specify the right combination of analysis and flight test to determine the acceleration levels at the pilot's station during continuous turbulence. Accordingly, proposed paragraph (e) of Appendix G is withdrawn. The current requirements related to operation in turbulence are adequate to determine the response at the pilot's station during continuous turbulence.

Proposal 8-62. For comments related to the proposal to add a new Appendix G to Part 25, see Proposal 8-25. Appendix G (redesignated Appendix H) to Part 25 is adopted with the changes discussed in Proposal 8-25.

Proposal 8-63. Final action on Proposal 8-63 was taken in Airworthiness Review Program, Amendment No. 7: Airframe Amendments (43 FR 50578; October 30, 1978).

Amendment to § 27.571. Because of the change to § 25.1529 adopted in this amendment, the reference to § 27.1529(a) (2) in §§ 27.571(b), (c), (d) (1), (d) (3), and (e) is no longer appropriate. The reference is changed to "§ A27.4 of Appendix A". This discrepancy was overlooked in Notice 75-31 (40 FR 29410; July 11, 1975). Since this amendment is clarifying in nature and does not impose a burden on the public, notice and public procedure are unnecessary and good cause exists for adopting this amendment.

Proposal 8-64. For comments related to the proposal to amend § 27.1529, see Proposal 8-21.

Proposals 8-65 and 8-66. Final action on Proposals 8-65 and 8-66 was taken in Airworthiness Review Program, Amendment No. 7: Airframe Amendments (43 FR 50578; October 30, 1978).

Proposal 8-67. For comments related to the proposal to add a new Appendix A to Part 27, see Proposal 8-25. Additional comments on this proposal, and on the proposal to add a new Appendix A to Part 29, are discussed here.

A commenter suggests that the wording of Appendix A be adjusted to take into account the differences between airplanes and rotorcraft. The FAA agrees. The appendix, as proposed, is generally equally applicable to airplanes and rotorcraft. However, several minor changes have been made to the appendix to provide for rotorcraft differences, primarily to cover rotors and differing fatigue standards.

A commenter objects to Appendix A, contending that: (1) The standards in current §§ 27.1529 and 29.1529 have been adequate in service, and (2) the proposal is excessive in scope and would create an undue burden. The FAA does not agree, having found that recommended maintenance procedures made available to operators/owners in the past were frequently inadequate in scope and content, providing no sound basis for maintaining the airworthiness of the rotorcraft. Appendix A, with the revisions and deletions discussed above and under Proposal 8-25, would not create an undue burden on the type certificate applicant.

One commenter expresses concern that certain inspection provisions in current § 91.217 might be applied to rotorcraft. The appendix contains no such requirement. Current § 91.217 applies only to certain airplanes.

Amendment to § 29.571. Because of the change to § 29.1529 adopted in this amendment, the reference to "§ 29.1529(a) (2)" in §§ 29.571(b), (c), (d) (1), (d) (3), and (e) is no longer appropriate. For consistency, the reference is changed to "§ A29.4 of Appendix A required by § 29.1529". This change was overlooked in Notice 75-31 (40 FR 29410; July

11, 1975). Since this amendment is clarifying in nature and does not impose a burden on the public, notice and public procedure are unnecessary and good cause exists for adopting this amendment.

Proposal 2-154. For a discussion directly related to proposed new § 29.783(g), see the discussion under Proposal 8-35 for § 25.783(g) (Proposal 2-59 of Notice 75-10). Section 29.783(g) is adopted without substantive change.

Proposals 8-68 through 8-76 and 2-164. Final action on Proposals 8-68, 8-69, 8-70, 8-71, 8-72, 8-73, 8-74, 8-75, 8-76, and 2-164 was taken in Airworthiness Review Program, Amendment No. 7: Airframe Amendments (43 FR 50578; October 30, 1978).

Proposal 8-77. For comments related to the proposal to amend § 29.1529, see Proposal 8-21.

Proposals 8-78 and 8-79. Final action on Proposals 8-78 and 8-79 was taken in Airworthiness Review Program, Amendment No. 7: Airframe Amendments (43 FR 50578; October 30, 1978).

Proposal 8-80. For comments related to the proposal to add a new Appendix A to Part 29, see Proposals 8-25 and 8-67.

Proposal 8-81. No unfavorable comments were received on adding a new § 31.12 providing for standardized application of the airworthiness requirements for balloons. Accordingly § 31.12 is adopted without substantive change.

Proposal 8-82. No unfavorable comments were received on adding a new § 31.16 requiring that balloon empty weight be determined. Accordingly, § 31.16 is adopted without substantive change.

Proposal 8-83. No unfavorable comments were received on the intent of new § 31.17 which specifies performance in terms of an initial minimum rate of climb. However, a commenter raises the question whether compliance with proposed § 31.17(a) could be shown by testing at several altitudes and ambient temperatures and then extrapolating, by appropriate analysis, to the other values in the range for which approval is sought. The FAA considers that such extrapolation by analysis is an acceptable means of complying with proposed § 31.17(a), because the climb performance of balloons is based on fundamental principles and, therefore, can be predicted with sufficient accuracy from established test points.

The FAA notes that the 300 fpm climb rate requirement in § 31.17(a) was intended as a minimum standard. To make this clear, § 31.17 as adopted is revised by inserting the words "at least" before the number "300" in the first sentence of § 31.17(a).

Proposal 8-84. A commenter, referring to new § 31.19(a) governing critical uncontrolled descent, suggests that it would be difficult and time-consuming to determine which tear is the most critical single tear in the balloon envelope between tear stoppers. The FAA does not agree. An analysis, or a combination of test and analysis, would be an acceptable means of determining the most critical single tear. It would not be necessary to test each kind of tear. No other unfavorable comments were received on the proposal to add a new § 31.19. Accordingly, § 31.19 is adopted without substantive change.

Proposal 8-85. No unfavorable comments were received on the proposal to amend § 31.27(c) to be consistent with new § 31.19, Performance: Uncontrolled descent. Accordingly, the proposal is adopted without substantive change.

Proposal 8-86. No unfavorable comments were received on the proposal to amend § 31.65 updating the position light standards and expressing them in language consistent with related standards in other airworthiness parts. However, the FAA finds that the use of a cross reference to § 23.1397 as proposed in § 31.65(e) may be inconvenient for those governed by Part 31. Accordingly, § 31.65, as adopted, sets forth the chromaticity coordinates for aviation red and aviation white as currently prescribed in § 23.1397.

Proposal 8-87. No unfavorable comments were received on the proposal to amend § 31.71. However, after further consideration, the FAA concludes that proposed § 31.71(a) (2) is unnecessarily restrictive in that it would, in all cases, require marking the

equipment as to its identification, function, *and* operating limitations. Marking of the equipment as to its identification, function, *or* operating limitations, or any applicable combination of those factors is sufficient. This is also the language used in corresponding sections of other aircraft airworthiness regulations. Section 31.71, as adopted, is revised accordingly.

Proposal 8-88. No unfavorable comments were received on the proposal to amend § 31.81 to detail operating limitations and information. The FAA notes, however, that proposed § 31.81(b) is not clear as to which "operating limitations and other information necessary for safe operation" must be furnished. The FAA's intent, as stated in the explanation, is to require that the information established under § 31.81(a) be furnished. Section 31.81(b) is revised accordingly. Section 31.81(a) is adopted without substantive change.

Proposal 8-89. A commenter is concerned that proposed § 31.82 might require balloon manufacturers to prepare two overlapping maintenance documents—the maintenance manual currently supplied to operators/owners, and the proposed Instructions for Continued Airworthiness. The FAA notes that under §§ 31.82 and 21.50(b), balloon manufacturers would be required to prepare and furnish only the Instructions for Continued Airworthiness.

The FAA notes further (as discussed under Proposal 8-21) that the Instructions for Continued Airworthiness need not be finalized until delivery of the first balloon, while § 31.82, as proposed, could be interpreted to require that they be finalized before type certification. This point is clarified in § 31.82, as adopted, consistent with the corresponding requirement in Parts 23, 25, 27, and 29.

Proposal 8-90. No unfavorable comments were received on the proposal to amend § 31.85(b) (1). However, a commenter questions whether percentage figures on the required fuel quantity gauge would be acceptable. The FAA has determined that, in the particular case of balloons (for which the fuel quantity information is to an extent less important to safety than for other classes of aircraft), calibration of the fuel quantity gauge in percent of fuel cell capacity is an acceptable means of complying with the last sentence of § 31.85(b) (1). Section 31.85(b) (1), as adopted, is revised to make this clear.

Proposal 8-91. No adverse comments were received on the proposal to add a new Appendix A to Part 31. However, comments received on the proposals to add a similar appendix to Parts 23, 25, 27, and 29 (Proposal 8-25), were equally valid with respect to this proposal. Accordingly, Appendix A to Part 31, as adopted, is revised in substance as applicable.

Regarding the proposals to require generalized repair data in the Instructions for Continued Airworthiness, it is more appropriate, as well as necessary and practicable, to include specific instructions for repair of the key elements of a balloon—the balloon envelope and its basket or trapeze. This information is incorporated in paragraph A31.3(i) as revised.

Proposal 8-92. A commenter objects to § 33.4 insofar as it would require completion of the Instructions for Continued Airworthiness before the type certificate is issued, contending that a significant portion of the data and other material called for is typically not compiled until 6 months or longer after type certification. The commenter suggests that manufacturers be allowed to prepare and make available the Instructions for Continued Airworthiness before the first aircraft equipped with the subject engine is put into service, which, it claims, is the earliest such instructions would be needed. Requiring the engine manufacturer to complete the Instructions for Continued Airworthiness before the type certificate is issued would constitute an unnecessary burden. However, the FAA considers that they must be made available, and furnished, upon delivery of the first engine on an aircraft or issuance of a standard certificate of airworthiness for the aircraft, whichever occurs later. This would be consistent with corresponding requirements proposed for other products. See Proposals 8-5 and 8-21. Section 33.4 is revised and adopted accordingly.

Proposal 8-93. A commenter observes that § 33.5 requires that the instruction manual for installing and operating the engine be "approved," whereas proposed § 33.4 requires that the Instructions for Continued Airworthiness be "acceptable to the Administrator," and recommends that the latter term be used for consistency. The FAA notes that the term "acceptable to the Administrator" is widely used in Part 43 in connection with maintenance requirements, whereas the term "approved" is more frequently used in FAR Parts containing installation and operating requirements. Considering the FAR as a whole, the FAA does not agree that such consistency is essential. Accordingly, § 33.5 is adopted as proposed.

Proposal 8-94. Several commenters object to proposed §§ 33.6(e) and (f), and to proposed §§ 23.1521(a) and 25.1521(a) (Proposals 8-20 and 8-56, respectively) on the grounds that the use of rated takeoff power or thrust for 10 minutes with one engine inoperative should not be limited to "the extent that the utilization is necessary for the airplane to avoid, without necessitating turning maneuvers, obstacles beneath the flight path intended for the airplane prior to the loss of the engine." In light of these comments and after further review, the FAA concludes that these proposals are premature and they are withdrawn.

In addition, the proposed transfer of the definitions for rated power and thrust from § 1.1 to proposed new § 33.6, Proposal 8-1, is withdrawn since the transfer may cause confusion in the administration of the aircraft certification requirements. Accordingly, Proposals 8-1, 8-20, 8-56, and 8-94 are withdrawn.

Proposal 8-95. For discussion of proposed § 33.19(b) see the discussion under Proposal 8-103. Revised § 33.19 is adopted without substantive change.

Amendment to §§ 33.55(c), 33.57(b), 33.93(b), and 33.99(b). Because of the deletion of §§ 33.5(c), (d), and (e), and the addition of a new § 33.4, the reference to "§ 33.5" in §§ 33.55(c), 33.57(b), 33.93(b), and 33.99(b) is no longer appropriate. For consistency, the reference is "§ 33.4." This change was inadvertently overlooked and was not proposed in Notice 75-31 (40 FR 29410; July 11, 1975). This editorial change corrects that discrepancy. Since this amendment is clarifying in nature and does not impose a burden on the public, notice and public procedure are unnecessary and good cause exists for adopting this amendment.

Proposal 8-97. A commenter recommends that § A33.3(a)(6) of Appendix A to Part 33 be revised by adding the words "requiring periodic attention" so as to make it clear that scheduling information is required solely for parts that require such attention. The language in this section is adequate. For parts not needing periodic attention, the applicant has only to state that parts not scheduled need not be serviced.

A commenter infers incorrectly that proposed §§ 43.16 and 91.163(c) apply only to rotorcraft. These regulations with the revision proposed also affect other classes of aircraft, as well as engines and propellers.

Some comments received on the proposed appendices for Parts 23, 25, 27, and 29 (Proposal 8-25) were equally valid with respect to proposed Appendix A to both Parts 33 and 35. Accordingly, the appendices to Parts 33 and 35 are revised in substance as applicable.

Proposal 8-98. For a discussion related to proposed § 35.3 see Proposal 8-93. A commenter observes that § 35.3 requires that the instruction manual for installing and operating the propeller be "approved," whereas § 35.4 requires that the Instructions for Continued Airworthiness be "acceptable to the Administrator," and recommends that the latter term be used for consistency. The FAA notes that the term "acceptable to the Administrator" is widely used in Part 43 in connection with maintenance requirements, while the term "approved" is more frequently used in FAR parts containing installation and operating requirements. Considering the FAR as a whole, the FAA does not agree that consistency is required in this instance. Accordingly, § 35.3 is adopted as proposed.

Proposal 8-99. In response to the concern of a commenter representing a number of Part 121 operators, the FAA notes that there is no requirement that any operator/owner use the Instructions for Continued Airworthiness referred to in proposed § 35.4. The new §§ 43.13(a), 43.16, and 91.163(c) allow the use of other methods. In particular, the use of maintenance manuals and continuous airworthiness maintenance programs developed under Parts 121, 123, 127, and 135, or an inspection program approved under § 91.217(e) would be acceptable alternatives to the Airworthiness Limitations section. This commenter suggests that language be added to proposed § 35.4 to make it clear that such alternatives may be used. The FAA agrees. The language in §§ 43.16 and 91.163(c) is revised accordingly.

Consistent with the discussion on proposed § 33.4 dealing with engines (see Proposal 8-92), the FAA finds that requiring the propeller manufacturer to complete the Instructions for Continued Airworthiness before the type certificate is issued would constitute an unnecessary burden. Accordingly, § 35.4 as adopted, requires that those instructions be made available and furnished upon delivery of the first aircraft with the propeller installed, or upon issuance of a standard certificate of airworthiness for an aircraft with the propeller installed, whichever occurs later.

Proposal 8-100. No unfavorable comments were received on the proposal to amend § 35.5 to more clearly indicate the basis for operating limitations and where they are listed. Accordingly, § 35.5 is adopted without substantive change.

Proposal 8-101. No unfavorable comments were received on the proposal to amend § 35.23 to provide an extreme low pitch indication. Accordingly, § 35.23 is adopted without substantive change.

Proposal 8-102. A commenter does not concur with the proposal to revise § 35.37 to require evaluation of metallic hubs and blades, stating that the words "must", "all", and "reasonably foreseeable" in the second sentence imply responsibility beyond current knowledge and the state of the art. The FAA does not agree. These terms are used in the current rule and the current state of the art defines the limits of the provision.

The same commenter recommends that § 35.37 be revised to apply to consideration of "normal and reasonably foreseeable load patterns," to account for the fact that only normal operations will or should be considered. The FAA does not agree. Load patterns which are reasonably foreseeable are critical and should be investigated even if they are not normal.

The same commenter also indicates that the third sentence should be revised to eliminate the term "reduction factors," since reduction factors are identified with only one particular method of presentation. The FAA agrees and the section is revised accordingly. This commenter finally states that the explanation implies that manufacturers have not taken permissible damage and material variation into account. This implication is not intended. It is the FAA's view that the fatigue evaluation should consider the occurrence of typical service damage and variation in material properties and the rule would provide for such an evaluation.

Another commenter suggests that the section be revised by adding certain technical requirements that are related to infinite component life. It is not necessary to specify requirements concerning infinite component life, since they are considered a normal part of propeller fatigue testing.

Section 35.37 is adopted as revised.

Proposal 8-103. A commenter objects to the proposal to add a new § 35.42 to define durability requirements for propeller blade pitch control system components, stating that the term "bench tests" in §§ 35.42(a) and (b) is too descriptive and restrictive. The FAA agrees that a reference to "bench tests" may be too restrictive. Other test methods may be equally acceptable in providing the necessary data. Accordingly, §§ 35.42(a) and (b) are revised to eliminate the specific reference to "bench."

The commenter also suggests that the words "in frequency and amplitude" be eliminated from § 35.42(a) since the words "cyclic testing" are fully descriptive. The FAA believes that these words are needed to prescribe key elements in the required test.

The commenter further suggests that the proposed testing to the equivalent of 1,000 hours of propeller operation is too restrictive in the case of a propeller with an overhaul period of less than 1,000 hours. The FAA considers the specific testing to be the minimum necessary to provide an acceptable safety level in service. The rule does not, however, prevent the selection of overhaul intervals of less than 1,000 hours.

Finally, the commenter suggests that the rule should permit an alternate of acceptance based upon service experience. The FAA recognizes that service experience can provide a statistical basis for determining component reliability. Its applicability, however, may vary according to such considerations as type of operation, the nature of the article under consideration, the degree of similarity between the reference article and the certification article, and the completeness of service records. Since it is dependent on such a variety of factors, the FAA does not agree that a specific alternative based on service experience should be included.

The proposal to add a new § 35.42, therefore, is adopted with the change discussed below. No adverse comments were received on the related proposed revisions to §§ 23.905, 25.905, and 33.19 to add the reference to new § 35.42, and the revisions are adopted.

Proposal 8-104. For comments related to the proposal to add a new Appendix A to Part 35, see Proposals 8-25 and 8-97.

A commenter objects to proposed § A35.1(c) of the appendix because the propeller owner (aircraft operator) would be wastefully provided with instructions and data that the propeller owner has no authority to use. The FAA does not agree. The Instructions for Continued Airworthiness must be furnished to the aircraft owner/operator who is the person responsible for maintaining the aircraft (including the propeller). The owner/operator may not be authorized to maintain the propeller, but the owner/operator can place the instructions in the hands of persons who are authorized.

The new Appendix A to Part 35, as adopted, is revised in accordance with comments discussed in Proposal 8-97.

Proposal 8-105. The proposed revision of § 43.9(a)(4) is being deferred for consideration in a forthcoming notice of proposed rule making of the Operations Review Program.

Proposal 8-106. A commenter representing a number of scheduled air carriers is concerned that the use of maintenance manuals and continued airworthiness programs developed under current § 121.133 and Subpart L of Part 121 (generally via Maintenance Review Board procedures), or under similar provisions of Parts 127 and 135, might not be acceptable as "other methods, techniques, and practices" under the terms of proposed § 43.13(a). This commenter suggests that language be added to proposed § 43.13(a) to make this clear. The FAA does not agree. The proposed language states that the use of such manuals and continued airworthiness programs is acceptable.

Proposal 8-107. A commenter representing a number of scheduled air carriers recommends that the Airworthiness Limitations section referred to in proposed § 43.16 include life limitations only and not inspections or other maintenance items. As discussed under Proposal 8-3, the FAA does not agree.

A commenter suggests that the words "or other methods, techniques; and practices acceptable to the Administrator" be added at the end of proposed § 43.16 to make it consistent with proposed § 43.13(a). The Airworthiness Limitations section contains specific mandatory replacement times and inspection intervals (with related procedures) that must be complied with, unless it can be shown by an operator with an approved maintenance program that these times are inappropriate for his operation. The use of alternatives not covered in the Airworthiness Limitations section would be allowed if

approved by the Administrator. Section 43.16 is revised to specifically state the alternatives to compliance with the Airworthiness Limitations section.

Proposal 8-108. No unfavorable comments were received on the proposal to amend § 45.11 to qualify, with respect to manned free balloons, the requirements in § 45.11(a) that deal with the location of the identification plate. Accordingly, the proposal is adopted without substantive change.

Proposal 8-109. No unfavorable comments were received on the proposal to amend § 45.13 to correctly reference §§ 45.11(a) and (b) with regard to identification plate requirements. Accordingly, the proposal is adopted without substantive change.

Proposal 8-110. A commenter representing a number of scheduled air carriers recommends that the words "inspection interval, or related procedure" be deleted from proposed § 45.14. The supporting rationale is the same as submitted by this commenter concerning Proposal 8-3 to amend § 21.31(c). As discussed under Proposal 8-3, the FAA disagrees.

The language in § 45.14 covers rotorcraft as well as airplanes, balloons, engines, and propellers. To make this clear, the word "Rotorcraft" is changed to "Manufacturer's".

Two commenters object to proposed § 45.14 on the grounds that it would be impracticable to mark small parts with a part and serial number. The FAA is not aware that the marking of small parts under current § 45.14 has presented a problem. In any event, the rule allows markings that are equivalent to part and serial numbers, such as symbols enabling the identification of the part as one for which a replacement time, inspection interval, or related procedure is specified in an Airworthiness Limitations section. Identification of such parts is clearly essential for safety. Accordingly, § 45.14 is adopted as revised.

Proposal 8-111. A commenter representing a number of scheduled air carriers recommends that the words "inspection interval, or related procedure" be deleted from proposed § 91.163(c). The supporting rationale is the same as that submitted by this commenter concerning Proposal 8-3 to amend § 21.31(c). As discussed under Proposal 8-3, the FAA disagrees. However, § 91.163(c) is revised to specifically identify the acceptable alternatives to compliance with the "Airworthiness Limitations" section.

The language in proposed § 91.163(c) covers rotorcraft as well as airplanes, balloons, engines, and propellers. To make this clear, the word "Rotorcraft" in § 91.163(c) has been changed to "Manufacturer's", and a statement has been added that operations specifications approved by the Administrator may be used in lieu of the Instructions for Continued Airworthiness. Section 91.163(c) is adopted as revised.

Proposal 8-112. No unfavorable comment was received on the proposal to amend § 91.165 to clarify maintenance personnel entries in maintenance records. Accordingly, the proposal is adopted without substantive change.

Proposal 8-113. Several commenters object to §§ 91.173(a)(2)(i) and (iii). A commenter states that adoption of the proposal would result in an inconsistency between § 91.173 and § 121.380, which contains the recordkeeping requirements for aircraft maintained under Part 121. The commenter also states that this inconsistency would cause great difficulty and economic hardship whenever an aircraft is sold by a Part 121 operator to a Part 91 operator and the Part 91 aircraft is maintained by a Part 121 operator under its repair station certificate. According to the commenter, the economic hardship would occur to both the Part 91 operator and the repair station. The same commenter contends that reliability information accumulated in recent years on transport category airplanes shows that there is no need for individualized total time records on equipment and components. Another commenter states that proposed requirements would result in large increases in maintenance costs for Part 91 operators and that only those components that are life-limited should have to carry total times.

The FAA concludes, however, that revision of § 91.173(a)(2)(i) would contribute significantly to safety with little burden on those affected. The currently prescribed record of total time in service for the airframe does not generally apply to the aircraft's engines

or propellers, since these components are frequently overhauled (or replaced) at different times. As a practical matter, it is known that operators of such aircraft normally keep records from which the total time in service of engines and propellers can be derived. Therefore, the FAA does not agree that the requirement to keep total times on engines and propellers would be a hardship and burden upon the operators. Accordingly, § 91.173(a) (2) (i) is adopted without change.

In light of the comment on proposed § 91.173(a) (2) (iii), the FAA has given further review of the proposal and has concluded that existing requirements satisfy the objective of the proposal. Accordingly proposed § 91.173(a) (2) (iii) is withdrawn.

The reporting and recordkeeping requirements contained in § 91.173 have been approved by the Office of Management and Budget in accordance with the Federal Reports Act of 1942.

Proposal 8-114. Several commenters agree with the intent of proposed § 91.193(c) (4) but suggest changes. A commenter suggests that the proposed installation instructions for hand fire extinguishers would be more appropriately placed in the type certification rules. The FAA does not agree. New type certification rules do not apply to aircraft already in service.

A commenter suggests that the words "unless obvious" be added to clarify when the hand fire extinguisher stowage provisions must be properly identified. The FAA agrees. Proposed § 91.193(c) (4) is revised and adopted accordingly.

Proposal 8-115. One commenter objects to the proposal to revise § 91.197(a) to require passenger information signs to meet the requirements of § 25.791. The commenter states that it is unnecessary, in many small general aviation aircraft operating under Subpart D of Part 91, to have such signs just for the sake of uniformity. The commenter also states that "nonstandard" signs now in use are wholly adequate to meet the needs of the type of operation. Finally, the commenter points out that installation costs for aircraft not currently having signs would be high and the pilot could just as easily announce the information as he could activate the signs.

Based on these comments and considering the type of operation involved, the FAA finds that the benefits associated with the proposal do not warrant its adoption. The proposal to revise § 91.197(a) is withdrawn.

Proposals 8-116, 8-117, 8-118, and 8-119. Final action on Proposals 8-116, 8-117, 8-118, and 8-119 was taken in Airworthiness Review Program, Amendment No. 8: Cabin Safety and Flight Attendant Amendments (45 FR 7750; February 4, 1980).

Proposal 8-120. In light of the need to conduct further testing of protective breathing equipment, the FAA withdraws its proposal to amend § 121.337, which will be addressed in an upcoming notice of proposed rule making.

ADOPTION OF THE AMENDMENT

Accordingly, Parts 11, 21, 23, 25, 27, 29, 31, 33, 35, 43, 45, and 91 of the Federal Aviation Regulations are amended, effective October 14, 1980.

(Sections 313(a), 601, 603, and 604 of the Federal Aviation Act of 1958 (49 U.S.C.1354(a), 1421, 1423, and 1424)); and Section 6(c) of the Department of Transportation Act (49 U.S.C.1655(c)))

The FAA has determined that this document involves a regulation which is not significant under Executive Order 12044, as implemented by Department of Transportation Regulatory Policies and Procedures (44 FR 11034; February 26, 1979). A copy of the final evaluation prepared for this document is contained in the docket. A copy of it may be obtained by writing to the individual and address listed in the "For Further Information Contact" paragraph.

---

§ 29.563 Structural ditching provisions.

Structural strength considerations of ditching must be in accordance with § 29.801(e).

FATIGUE EVALUATION

§ 29.571 Fatigue evaluation of flight structure.

(a) *General.* Each portion of the flight structure (the flight structure includes rotors, rotor drive systems between the engines and the rotor hubs, controls, fuselage, and their related primary attachments) the failure of which could be catastrophic, must be identified and must be evaluated under paragraph (b), (c), (d) or (e) of this section. The following apply to each fatigue evaluation:

(1) The procedure for the evaluation must be approved.

(2) The locations of probable failure must be determined.

(3) Inflight measurement must be included in determining the following:

(i) Loads or stresses in all critical conditions throughout the range of limitations in § 29.309, except that maneuvering load factors need not exceed the maximum values expected in operation.

(ii) The effect of altitude upon these loads or stresses.

(4) The loading spectra must be as severe as those expected in operation and must be based on loads or stresses determined under subparagraph (3) of this paragraph.

(b) *Fatigue tolerance evaluation.* It must be shown that the fatigue tolerance of the structure ensures that the probability of catastrophic fatigue failure is extremely remote without establishing replacement times, inspection intervals or other procedures under [§ A29.4 of Appendix A.]

(c) *Replacement time evaluation.* It must be shown that the probability of catastrophic fatigue failure is extremely remote within a replacement time furnished under [§ A29.4 of Appendix A.]

(d) *Failsafe evaluation.* The following apply to failsafe evaluations:

(1) It must be shown that all partial failures will become readily detectable under inspection procedures furnished under § 29.1529(a)(2).

(2) The interval between the time when any partial failure becomes readily detectable under subparagraph (1), and the time when any such failure is expected to reduce the remaining strength of the structure to limit or maximum attainable loads (whichever is less), must be determined.

(3) It must be shown that the interval determined under subparagraph (2) is long enough, in relation to the inspection intervals and related procedures furnished under § 29.1529(a)(2), to provide a probability of detection great enough to ensure that the probability of catastrophic failure is extremely remote.

(e) *Combination of replacement time and failsafe evaluations.* A component may be evaluated under a combination of paragraphs (c) and (d) of this section. For such component it must be shown that the probability of catastrophic failure is extremely remote with an approved combination of replacement time, inspection intervals, and related procedures furnished under § 29.1529(a)(2).

Subpart D—Design and Construction

GENERAL

§ 29.601 Design.

(a) The rotorcraft may have no design features or details that experience has shown to be hazardous or unreliable.

(b) The suitability of each questionable design detail and part must be established by tests.

§ 29.603 Materials.

The suitability and durability of materials used for parts, the failure of which could adversely affect safety, must—

(a) Be established on the basis of experience or tests;

(b) Meet approved specifications that ensure their having the strength and other properties assumed in the design data; and

[(c) Take into account the effects of environmental conditions, such as temperature and humidity, expected in service.]

§ 29.605 Fabrication methods.

[(a)] The methods of fabrication used must produce consistently sound structures. If a fabrication process (such as gluing, spot welding, or heat-treating) requires close control to reach this objective, the process must be performed according to an approved process specification.

[(b) Each new aircraft fabrication method must be substantiated by a test program.]

(c) Adequate to—

(1) Counteract any normal unbalanced torque when starting or stopping the rotor; and

(2) Hold the rotorcraft parked on a 10 degree slope on a dry, smooth pavement.

§ 29.737 Skis.

(a) The maximum limit load rating of each ski must equal or exceed the maximum limit load determined under the applicable ground load requirements of this Part.

(b) There must be a stabilizing means to maintain the ski in an appropriate position during flight. This means must have enough strength to withstand the maximum aerodynamic and inertia loads on the ski.

FLOATS AND HULLS

§ 29.751 Main float buoyancy.

(a) For main floats, the buoyancy necessary to support the maximum weight of the rotorcraft in fresh water must be exceeded by—

(1) 50 percent, for single floats; and

(2) 60 percent, for multiple floats.

(b) Each main float must have enough water-tight compartments so that, with any single main float compartment flooded, the mainfloats will provide a margin of positive stabiity great enough to minimize the probability of capsizing.

§ 29.753 Main float design.

(a) *Bag floats.* Each bag float must be designed to withstand—

(1) The maximum pressure differential that might be developed at the maximum altitude for which certification with the float is requested; and

(2) The vertical loads prescribed in § 29.521(a), distributed along the length of the bag over three-quarters of its projected area.

(b) *Rigid floats.* Each rigid float must be able to withstand the vertical, horizontal and side loads prescribed in § 29.521. An approriate load distribution under critical conditions must be used.

§ 29.755 Hull buoyancy.

(a) *Water-based and amphibian rotorcraft.* The hull and auxiliary floats, if used, must have enough watertight compartments so that, with any single compartment of the hull or auxiliary floats flooded, the buoyancy of the hull and auxiliary floats, and wheel tires if used, provides a margin of positive water stability great enough to minimize the probability of capsizing the rotorcraft for the worst combination of wave heights and surface winds for which approval is desired.

(b) *Limited amphibian rotorcraft.* For limited amphibian rotorcraft, the following apply:

(1) The hull and auxiliary floats, if used, must be divided into compartments so that, with any single compartment located in the likely area of water impact during landing flooded, the buoyancy of the hull and auxiliary floats, and wheel tires if used, will provide a sufficient margin of positive water stability to minimize the probability of capsizing the rotorcraft.

(2) The rotorcraft must remain afloat, after a landing on water, for at least one-half hour.

(3) The requirements of subparagraphs (1) and (2) of this paragraph apply considering the most severe combination of wave heights and wind conditions for which approval is desired.

§ 29.757 Hull and auxiliary float strength.

The hull, and auxiliary floats if used, must withstand the water loads prescribed by § 29.519 with a rational and conservative distribution of local and distributed water pressures over the hull and float bottom.

PERSONNEL AND CARGO ACCOMMODATIONS

§ 29.771 Pilot compartment.

For each pilot compartment—

(a) The compartment and its equipment must allow each pilot to perform his duties without unreasonable concentration or fatigue;

(b) If there is provision for a second pilot, the rotorcraft must be controllable with equal safety from either pilot seat;

(c) The vibration and noise characteristics of cockpit appurtenances may not interfere with safe operation;

(d) Inflight leakage of rain or snow that could distract the crew or harm the structure must be prevented.

§ 29.773 Pilot compartment view.

(a) *Nonprecipitation conditions.* For nonprecipitation conditions, the following apply:

(1) Each pilot compartment must be arranged to give the pilots a sufficiently extensive, clear, and undistorted view for safe operation.

(2) Each pilot compartment must be free of glare and reflection that could interfere with the pilot's view. If certification for night operation is requested, this must be shown by night flight tests.

(b) *Precipitation conditions.* For precipitation conditions, the following apply:

(1) Each pilot must have a sufficiently extensive view for safe operation—

(i) In heavy rain at forward speeds up to V_H; and

(ii) In the most severe icing condition for which certification is requested.

(2) The first pilot must have a window that—

(i) Is openable under the conditions prescribed in subparagraph (1) of this paragraph; and

(ii) Provides the view prescribed in that subparagraph.

§ 29.775 Windshield and windows.

Nonsplintering safety glass must be used in glass windshields and windows.

§ 29.777 Cockpit controls.

Cockpit controls must be—

(a) Located to provide convenient operation and to prevent confusion and inadvertent operation; and

(b) Located and arranged with respect to the pilot's seats so that there is full and unrestricted movement of each control without interference from the cockpit structure or the pilot's clothing when pilots from 5′2″ to 6′0″ in height are seated.

§ 29.783 Doors.

(a) Each closed cabin must have at least one adequate and easily accessible external door.

(b) No passenger door may be located with respect to any rotor disc so as to endanger persons following appropriate instructions for the use of that door.

(c) There must be means for locking crew and external passenger doors and for preventing their opening in flight inadvertently or as a result of mechanical failure. It must be possible to open external doors from inside and outside the cabin with the rotorcraft on the ground. The means of opening must be simple, obvious, and so arranged and marked that it can be readily located and operated.

(d) There must be reasonable provisions to prevent the jamming of any external door, in a minor crash, as a result of fuselage deformation.

(e) There must be means for direct visual inspection of the locking mechanism by crewmembers to determine whether the external doors (including passenger, crew, service, and cargo doors) are fully locked. There must be visual means to signal to appropriate crewmembers when normally used external doors are closed and fully locked.

(f) For outward opening external doors usable for entrance or egress, there must be an auxiliary safety latching device to prevent the door from opening when the primary latching mechanism fails. If the door does not meet the requirements of paragraph (c) of this section with this device in place, suitable operating procedures must be established to prevent the use of the device during takeoff and landing.

[(g) If an integral stair is installed in a passenger entry door that is qualified as a passenger emergency exit, the stair must be designed so that under the following conditions

the effectiveness of passenger emergency egress will not be impaired:

[(1) The door, integral stair, and operating mechanism have been subjected to the inertia forces specified in § 29.561(b)(3), acting separately relative to the surrounding structure.

[(2) The rotorcraft is in the normal ground attitude and in each of the attitudes corresponding to collapse of one or more legs, or primary members, as applicable, of the landing gear.]

§ 29.785 Seats, safety belts, and harnesses.

(a) The seats, safety belts, shoulder harnesses, and adjacent parts of the rotorcraft, at each station designated for occupancy during takeoff and landing, must be designed so that a person making proper use of these facilities will not suffer serious injury in an emergency landing as a result of the inertia forces specified in § 29.561.

(b) Each seat must be approved.

INTENTIONALLY LEFT BLANK

(i) The cylinder head or coolant outlet (for reciprocating engines);

(ii) The engine oil; and

(iii) The transmission oil.

(d) *Fuel grade or designation.* The minimum fuel grade (for reciprocating engines) or fuel designation (for turbine engines) must be established so that it is not less than that required for the operation of the engines within the limitations in paragraphs (b) and (c) of this section.

(e) *Ambient temperature.* Ambient temperature limitations (including limitations for winterization installations if applicable) must be established as the maximum ambient atmospheric temperature at which compliance with the cooling provisions of §§ 29.1041 through 29.1049 is shown.

(f) *Two and one-half-minute power operation.* For helicopters for which compliance with the 2½-minute power requirements of this Part is shown, the established time limit for the use of 2½-minute power must be 2½ minutes for any period in which that power is used. The use of 2½-minute power must also be limited by—

(1) The maximum rotational speed, which may not be greater than—

(i) The maximum value determined by the rotor design; or

(ii) The maximum value shown during the type tests;

(2) The maximum allowable gas temperature;

(3) The maximum allowable torque; and

(4) The maximum allowable oil temperature.

(g) *Thirty-minute power operation.* For helicopters for which compliance with the 30-minute power requirements of this Part is shown, the established time limit for the use of 30-minute power must be 30 minutes for any period in which that power is used. The use of 30-minute power must also be limited by—

(1) The maximum rotational speed which may not be greater than—

(i) The maximum value determined by the rotor design; or

(ii) The maximum value shown during the type tests;

(2) The maximum allowable gas temperature;

(3) The maximum allowable torque; and

(4) The maximum allowable oil temperature.

§ 29.1522 Auxiliary power unit limitations.

If an auxiliary power unit that meets the requirements of TSO-C77 is installed in the rotorcraft, the limitations established for that auxiliary power unit under the TSO including the categories of operation must be specified as operating limitations for the rotorcraft.

§ 29.1523 Minimum flight crew.

The minimum flight crew must be established so that it is sufficient for safe operation, considering—

(a) The workload on individual crewmembers;

(b) The accessibility and ease of operation of necessary controls by the appropriate crewmember; and

(c) The kinds of operation authorized under § 29.1525.

§ 29.1525 Kinds of operation.

The kinds of operation to which the rotorcraft is limited are established by the flight characteristics and installed equipment.

§ 29.1527 Maximum operating altitude.

The maximum altitude up to which operation is allowed, as limited by flight, structural, powerplant, functional, or equipment characteristics, must be established.

[§ 29.1529 Instructions for Continued Airworthiness.

[The applicant must prepare Instructions for Continued Airworthiness in accordance with

Appendix A to this Part that are acceptable to the Administrator. The instructions may be incomplete at type certification if a program exists to ensure their completion prior to delivery of the first rotorcraft or issuance of a standard certificate of airworthiness, whichever occurs later.]

MARKINGS AND PLACARDS

§ 29.1541 General.

(a) The rotorcraft must contain—

(1) The markings and placards specified in §§ 29.1545 through 29.1565; and

(2) Any additional information, instrument markings, and placards required for the safe operation of the rotorcraft if it has unusual design, operating or handling characteristics.

(b) Each marking and placard prescribed in paragraph (a) of this section—

(1) Must be displayed in a conspicuous place; and

(2) May not be easily erased, disfigured, or obscured.

§ 29.1543 Instrument markings: general.

For each instrument—

(a) When markings are on the cover glass of the instrument there must be means to maintain the correct alignment of the glass cover with the face of the dial; and

(b) Each arc and line must be wide enough and located to be clearly visible to the pilot.

§ 29.1545 Airspeed indicator.

(a) Each airspeed indicator must be marked as specified in paragraph (b) of this section, with the marks located at the corresponding indicated airspeeds.

(b) The following markings must be made:

(1) A red radial line—

(i) For rotorcraft other than helicopters, at V_{NE}; and

(ii) For helicopters, at V_{NE} (power-on).

(2) A red, cross-hatched radial line at V_{NE} (power-off) for helicopters, if V_{NE} (power-off) is less than V_{NE} (power-on).

(3) For the caution range, a yellow arc.

(4) For the safe operating range, a green arc.

§ 29.1547 Magnetic direction indicator.

(a) A placard meeting the requirements of this section must be installed on or near the magnetic direction indicator.

(b) The placard must show the calibration of the instrument in level flight with the engines operating.

(c) The placard must state whether the calibration was made with radio receivers on or off.

(d) Each calibration reading must be in terms of magnetic heading in not more than 45° increments.

§ 29.1549 Powerplant instruments.

For each required powerplant instrument, as appropriate to the type of instruments—

(a) Each maximum and, if applicable, minimum safe operating limit must be marked with a red radial or a red line;

(b) Each normal operating range must be marked with a green arc or green line, not extending beyond the maximum and minimum safe limits;

(c) Each takeoff and precautionary range must be marked with a yellow arc or yellow line; and

(d) Each engine or propeller range that is restricted because of excessive vibration stresses must be marked with red arcs or red lines.

§ 29.1551 Oil quantity indicator.

Each oil quantity indicator must be marked with enough increments to indicate readily and accurately the quantity of oil.

§ 29.1553 Fuel quantity indicator.

If the unusable fuel supply for any tank exceeds one gallon, or five percent of the tank capacity, whichever is greater, a red arc must be marked on its indicator extending from the calibrated zero reading to the lowest reading obtainable in level flight.

§ 29.1555 Control markings.

(a) Each cockpit control must be plainly marked as to its function and method of operation.

(b) For powerplant fuel controls—

(1) Each fuel tank selector valve control must be marked to indicate the position corresponding to each tank and to each existing cross feed position;

(2) If safe operation requires the use of any tanks in a specific sequence, that sequence must be marked on, or adjacent to, the selector for those tanks; and

(3) Each valve control for any engine of a multiengine rotorcraft must be marked to indicate the position corresponding to each engine controlled.

(c) Usable fuel capacity must be marked as follows:

(1) For fuel systems having no selector controls, the usable fuel capacity of the system must be indicated at the fuel quantity indicator.

(2) For fuel systems having selector controls, the usable fuel capacity available at each selector control position must be indicated near the selector control.

(d) For accessory, auxiliary, and emergency controls—

(1) Each essential visual position indicator, such as those showing rotor pitch or landing gear position, must be marked so that each crewmember can determine at any time the position of the unit to which it relates; and

(2) Each emergency control must be red and must be marked as to method of operation.

§ 29.1557 Miscellaneous markings and placards.

(a) *Baggage and cargo compartments, and ballast location.* Each baggage and cargo compartment, and each ballast location must have a placard stating any limitations on contents, including weight, that are necessary under the loading requirements.

(b) *Seats.* If the maximum allowable weight to be carried in a seat is less than 170 pounds, a placard stating the lesser weight must be permanently attached to the seat structure.

(c) *Fuel and oil filler openings.* The following apply:

(1) Fuel filler openings must be marked at or near the filler cover with—

(i) The word "fuel";

(ii) For reciprocating engine powered rotorcraft, the minimum fuel grade;

(iii) For turbine engine powered rotorcraft, the permissible fuel designations; and

(iv) For pressure fueling systems, the maximum permissible fueling supply pressure and the maximum permissible defueling pressure.

(2) Oil filler openings must be marked at or near the filler cover with the word "oil."

(d) *Emergency exit placards.* Each placard and operating control for each emergency exit must differ in color from the surrounding fuselage surface as prescribed in § 29.811(h)(2). A placard must be near each emergency exit control and must clearly indicate the location of that exit and its method of operation.

§ 29.1559 Limitations placard.

There must be a placard in a clear view of the pilot stating: "This (helicopter, gyrodyne, etc.) must be operated in compliance with the operating limitations specified in the FAA approved Rotorcraft Flight Manual." If the Rotorcraft Maintenance Manual contains an

"Airworthiness Limitations" section issued under § 29.1529(a)(2), the placard must contain the following additional statement: "The 'Airworthiness Limitations' section of the Rotorcraft Maintenance Manual must be complied with."

§ 29.1561 Safety equipment.

(a) Each safety equipment control to be operated by the crew in emergency, such as controls for automatic liferaft releases, must be plainly marked as to its method of operation.

(b) Each location, such as a locker or compartment, that carries any fire extinguishing, signaling, or other life saving equipment, must be so marked.

(c) Stowage provisions for required emergency equipment must be conspicuously marked to identify the contents and facilitate removal of the equipment.

(d) Each liferaft must have obviously marked operating instructions.

(e) Approved survival equipment must be marked for identification and method of operation.

§ 29.1565 Tail rotor.

Each tail rotor must be marked so that its disc is conspicuous under normal daylight ground conditions.

ROTORCRAFT FLIGHT MANUAL

§ 29.1581 General.

(a) *Furnishing information.* A Rotorcraft Flight Manual must be furnished with each rotorcraft, and it must contain the following:

(1) Information required by §§ 29.1583 through 29.1589.

(2) Other information that is necessary for safe operation because of design, operating, or handling characteristics.

(b) *Approved information.* Each part of the manual listed in §§ 29.1583 through 29.1589 that is appropriate to the rotorcraft, must be furnished, verified, and approved, and must be segregated, identified, and clearly distinguished from each unapproved part of that manual.

(c) [Reserved]

(d) *Table of contents.* Each Rotorcraft Flight Manual must include a table of contents if the complexity of the manual indicates a need for it.

§ 29.1583 Operating limitations.

(a) *Airspeed and rotor limitations.* Information necessary for the marking of airspeed and rotor limitations on or near their respective indicators must be furnished. The significance of each limitation and of the color coding must be explained.

(b) *Powerplant limitations.* The following information must be furnished:

(1) Limitations required by § 29.1521.

(2) Explanation of the limitations, when appropriate.

(3) Information necessary for marking the instruments required by §§ 29.1549 through 29.1553.

(c) *Weight and loading distribution.* The weight and center of gravity limits required by §§ 29.25 and 29.27, respectively, must be furnished. If the variety of possible loading conditions warrants, instructions must be included to allow ready observance of the limitations.

(d) *Flight crews.* When a flight crew of more than one is required, the number and functions of the minimum flight crew determined under § 29.1523 must be furnished.

(e) *Kinds of operation.* Each kind of operation for which the rotorcraft and its equipment installations are approved must be listed.

(f) *Limiting heights.* Enough information must be furnished to allow compliance with § 29.1517.

[(g) [Reserved]]

(h) *Altitude.* The altitude established under § 29.1527 and an explanation of the limiting factors must be furnished.

[Appendix A

[Instructions For Continued Airworthiness

[A29.1 *General.*

[(a) This appendix specifies requirements for the preparation of Instructions for Continued Airworthiness as required by § 29.1529.

[(b) The Instructions for Continued Airworthiness for each rotorcraft must include the Instructions for Continued Airworthiness for each engine and rotor (hereinafter designated 'products'), for each appliance required by this chapter, and any required information relating to the interface of those appliances and products with the rotorcraft. If Instructions for Continued Airworthiness are not supplied by the manufacturer of an appliance or product installed in the rotorcraft, the Instructions for Continued Airworthiness for the rotorcraft must include the information essential to the continued airworthiness of the rotorcraft.

[(c) The applicant must submit to the FAA a program to show how changes to the Instructions for Continued Airworthiness made by the applicant or by the manufacturers of products and appliances installed in the rotorcraft will be distributed.

[A29.2 *Format.*

[(a) The Instructions for Continued Airworthiness must be in the form of a manual or manuals as appropriate for the quantity of data to be provided.

[(b) The format of the manual or manuals must provide for a practical arrangement.

[A29.3 *Content.*

[The contents of the manual or manuals must be prepared in the English language. The Instructions for Continued Airworthiness must contain the following manuals or sections, as appropriate, and information:

[(a) *Rotorcraft maintenance manual or section.*

[(1) Introduction information that includes an explanation of the rotorcraft's features and data to the extent necessary for maintenance or preventive maintenance.

[(2) A description of the rotorcraft and its systems and installations including its engines, rotors, and appliances.

[(3) Basic control and operation information describing how the rotorcraft components and systems are controlled and how they operate, including any special procedures and limitations that apply.

[(4) Servicing information that covers details regarding servicing points, capacities of tanks, reservoirs, types of fluids to be used, pressures applicable to the various systems, location of access panels for inspection and servicing, locations of lubrication points, the lubricants to be used, equipment required for servicing, tow instructions and limitations, mooring, jacking, and leveling information.

[(b) *Maintenance Instructions.*

[(1) Scheduling information for each part of the rotorcraft and its engines, auxiliary power units, rotors, accessories, instruments, and equipment that provides the recommended periods at which they should be cleaned, inspected, adjusted, tested, and lubricated, and the degree of inspection, the applicable wear tolerances, and work recommended at these periods. However, the applicant may refer to an accessory, instrument, or equipment manufacturer as the source of this information if the applicant shows that the item has an exceptionally high degree of complexity requiring specialized techniques, test equipment, or expertise. The recommended overhaul periods and necessary cross references to the Airworthiness Limitations section of the manual must also be included. In addition, the applicant must include an inspection program that includes the frequency and extent of the inspections necessary to provide for the continued airworthiness of the rotorcraft.

[(2) Troubleshooting information describing probable malfunctions, how to recognize those malfunctions, and the remedial action for those malfunctions.

[(3) Information describing the order and method of removing and replacing products and parts with any necessary precautions to be taken.

[(4) Other general procedural instructions including procedures for system testing during ground running, symmetry checks, weighing and determining the center of gravity, lifting and shoring, and storage limitations.

[(c) Diagrams of structural access plates and information needed to gain access for inspections when access plates are not provided.

[(d) Details for the application of special inspection techniques including radiographic and ultrasonic testing where such processes are specified.

[(e) Information needed to apply protective treatments to the structure after inspection.

[(f) All data relative to structural fasteners such as identification, discard recommendations, and torque values.

[(g) A list of special tools needed.

[A29.4 *Airworthiness Limitations section.*

[The Instructions for Continued Airworthiness must contain a section titled Airworthiness Limitations that is segregated and clearly distinguishable from the rest of the document. This section must set forth each mandatory replacement time, structural inspection interval, and related structural inspection procedure approved under § 29.571. If the Instructions for Continued Airworthiness consist of multiple documents, the section required by this paragraph must be included in the principal manual. This section must contain a legible statement in a prominent location that reads: "The Airworthiness Limitations section is FAA approved and specifies maintenance required under §§ 43.16 and 91.163 of the Federal Aviation Regulations unless an alternative program has been FAA approved."]

☆U.S. GOVERNMENT PRINTING OFFICE : 1980 - 341-443/61